

7000 Series Miniature Rocker & Lever Handle Switches



Features/Benefits

- Multi-pole and multi-position
- Wide variety of actuator and termination options
- Epoxy terminal-seal compatible with bottom wash cleaning
- Contact Rating Gold 0.4 VA MAX. @ 20 V AC OR DC MAX.


Typical Applications

- Telecommunications
- Instrumentation
- Medical equipment

Silver 5 AMPS @ 120 V AC OR 28 V DC; 2 AMPS @ 250 V AC

Part Number	Function	Actuator	Terminations	Contact Material	Electrical Life
7101J1AV2QE2	SP On-None-On	.531" long rocker	Vertical right angle, PC thru-hole	Silver	100,000 cycles
7101J1AQE2	SP On-None-On	.531" long rocker	Right angle, PC thru-hole	Silver	100,000 cycles
7101J1ABE2	SP On-None-On	.531" long rocker	Right angle, PC thru-hole	Gold	100,000 cycles

E Series Sealed Miniature Rocker and Lever Handle Switches



Features/Benefits

- Sealed against solder and cleaning process contaminants
- ESD Resistance—all actuator options
- Rocker, case & bushing UL 94V-0
- Contact Rating 7.5 AMPS@125 V AC or 28 V DC; 3 AMPS @ 250 V AC

Typical Applications

- Telecommunications
- Instrumentation
- Computers & peripherals

Part Number	Function	Actuator	Terminations	Contact Material	Electrical Life
E101J1AQE2	SP On-None-On	.531" long rocker	Right angle, PC thru-hole	Silver	40,000 cycles
E201J1V31QE2	DP On-None-On	.531" long rocker	.460" high, V-bracket, snap-in	Silver	40,000 cycles
E101J3V31QE2	SP On-None-On	.906" long rocker	.460" high, V-bracket, snap-in	Silver	40,000 cycles

D Series Miniature Snap-in Power Rocker Switches



Features/Benefits

- Momentary and maintained models
- PC and quick connect terminals
- Recessed bracket available — prevents accidental actuation
- Contact Rating 10 AMPS @ 125 V AC; 5 AMPS @ 250 V AC

Typical Applications

- Small appliances
- Computers and peripherals
- Medical instrumentation

Part Number	Function	Mounting Style/Color	Terminations	Contact Material	Electrical Life
D502J12S2AHQF	SPST, On-None-Off	Snap-in, black	Right angle, PC thru-hole	Silver	10,000 cycles
D101J12S215PQF	SPDT, On-None-On	Snap-in, black	PC thru-hole	Silver	10,000 cycles
D501J12S2AHQF	SPDT, On-None-On	Snap-in, black	Right angle, PC thru-hole	Silver	10,000 cycles

Note - this catalog represents a small sample of C&K part numbers. C&K has over 55,000 part numbers available.

Please refer to the C&K full line catalog for a complete list of products and configurations.

Dimensions and specifications subject to change.

CA Series Illuminated and Non-illuminated Power Rocker Switches



Features/Benefits

- Cosmetic slimline detail
- Positive detent
- Contact Rating 15 AMPS @ 125 V AC; 10 AMPS @ 250 V AC; 1/4 HP @ 125 V AC or 250 V AC

Typical Applications

- Hair dryers and other small appliances
- HVAC and other large appliances

Part Number	Function	Actuator	Illumination	Actuator Markings	Terminations	Contact Material	Electrical Life
CA04J137207PQ	SPST, On-Off	Red translucent with 125 V lamp	Red	O –	Quick connect	Silver	10,000 cycles
CA01J12207PQ	SPDT, On-On	Rocker with gloss finish, black	None	O –	Quick connect	Silver	10,000 cycles
CA04J167207Q	SPST, On-Off	Red translucent with 125 V lamp	Green		Quick connect	Silver	10,000 cycles

DF Series Power Rocker



Features/Benefits

- Power switching up to 16 AMPS
- Sub-panel and Front-panel mounting
- Multi-position and multi-pole function
- Available in UL94V-0 grade materials
- Contact Rating 16 AMPS @ 125, 250 V AC; 1/4 HP @ 125 V AC; 1/2 HP @ 250 V AC; 6 AMPS @ 48 V DC (UL/CSA)

Typical Applications

- Computers
- Power supplies
- Appliances
- Fitness equipment
- Off-road vehicles

Part Number	Function	Housing Style/Color	Terminations	Contact Material	Electrical Life
DF62J12S2AHQA	DPST, Off-On	Sub-panel, black	Right angle, PC thru-hole	Silver (UL/CSA)	10,000 cycles
DF62J12S2APQF	DPST, Off-On	Sub-panel, black	Right angle, PC thru-hole	Silver (UL/CSA/VDE)	10,000 cycles
DF62J12S215PQF	DPST, Off-On	Sub-panel, black	Quick connect	Silver (UL/CSA/VDE)	10,000 cycles

SW Series Power Rocker



Features/Benefits

- Oval shape
- Several color options (black, white, almond, biscuit)
- Front panel mounting
- Contact rating 6.5 AMP @ 125 V AC

Typical Applications

- Overhead fan on range / hood
- Small and large appliances

Part Number	Function	Actuator	Actuator Marking	Terminations
SW-13A65N-A01 BK	SPDT, On-Off-On	Concave (Curved)	No Marking	Quick Connect

Note - this catalog represents a small sample of C&K part numbers. C&K has over 55,000 part numbers available.

Please refer to the C&K full line catalog for a complete list of products and configurations.

Dimensions and specifications subject to change.