

# LARGE TRIM, 2-WAY PUSHBUTTON

## MULTI-POSITION TOGGLE PLUS PUSHBUTTON, COMMERCIAL & MILITARY GRADES

The T2 series provides two functions in one compact switch: toggle and pushbutton action. Features toggle lockout when pushbutton mode is actuated and pushbutton lockout when in toggle mode. A resilient seal in the plunger provides splashproof and dusttight seal.

### T2-0004

**Operating Force:** 24 +/- 10 oz  
**Circuit:** DPDT-NO, ON-OFF-ON  
 No pushbutton function  
**Rating:** 5 amps Resistive  
 3 amps Inductive  
 1 amp Lamp  
 Logic Level: 2mA @ 15VDC  
**Mechanical Life:** 100,000 cycles  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Gray thermoplastic  
**Case:** Black anodized aluminum



### T2-0034

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: SPNO double break  
**Rating:** 1A to 50mA Resistive @ 4-28VDC  
**Electrical Life:** 100,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Gray nylon  
**Case:** Black anodized aluminum alloy



### T2-0008

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Button:** Black nylon  
**Case:** Black anodized aluminum



### T2-0018

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1 amp Resistive  
 0.5 amp Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T2-0009

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** Toggle: 10 amps Resistive / 5 amps Inductive  
 Pushbutton: 10 amps Resistive / 3 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T2-0047

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



### T2-0015

**Operating Force:** Toggle: 5.0 lbs.  
 Pushbutton: 4.0 lbs.  
**Circuit:** Toggle: SPST-NO, 4-position, center OFF, momentary  
 Pushbutton: SPST-NO  
**Rating:** 2 amps Resistive  
 2 amps Inductive  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T2-0044

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 3.75 lbs.  
**Circuit:** Toggle: DPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 0.1mA to 500mA Resistive @ 5-32VDC  
 0.1mA to 500mA Inductive @ 5-32VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 2, dusttight per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Dry black chrome plated aluminum alloy



### T2-0016

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 4, resilient per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T2-0045

**Operating Force:** Toggle: 2.5 lbs.  
 Pushbutton: 4.5 lbs.  
**Circuit:** Toggle: SPST-NO, ON-OFF-ON  
 Pushbutton: DPST-NO double break  
**Rating:** 1mA to 250mA Resistive @ 12-28VDC  
**Electrical Life:** 50,000 cycles  
**Seal:** Enclosure Design 3, watertight per MIL-PRF-8805  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy

