

SQI 2,5/2 RD

17201.9



Insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 9.9 mm, Rated cross-section: 2.5 mm², Colour: Red

Commercial

General

Colour: Red

Country of origin: DE

Customs number: 85389099

Packaging unit: 50

Product description: Insulated cross-connector

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 1.23g

Weight per piece (not including packaging): 1.2g

Technical

Dimensions

Height: 23mm

Length: 4mm

Pitch size: 5mm

Width: 9.9mm

Ratings

Contamination degree: 2

Current load, max.: 32A

Rated cross-section: 2.5mm²

Rated current: 24A

Voltage with partition, max.: 1000V

Voltage without partition, max.: 1000V

Connection data

No. of poles: 2

Further technical data

Insulation available: 1

Mounting type: Plug in

Number of bridged terminals: 2

Touch protection is available: 1

Materials

Flammability class UL 94: V-2

Insulation housing: Polyamide 6.6

Material: Bronze

Working temperature, max.: 105°C

Working temperature, min.: -40°C

Approvals

Environment

Environmental Product Compliance

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2024-06-27

RoHS Conform: Yes

Accessories

Insulation cap for cross-connector

Terminals with screw connection system




SSLD 2,5 GNYE

17182.2



SRKD 2,5 BG

17180.2



SRKD 2,5/SV BG

17181.2



SRK B 2,5/2A BG

17101.2

Terminal blocks



SSL 2,5/2A GNYE

17103.2



SRK 2,5/2A RB

17100.0



SRK 2,5/2A/PE BKYE

17129.2



SRK 2,5/2A/Z BG

17102.2
