



**604001100**

Cable reductions

MADE IN ITALY



#### GENERAL DESCRIPTION

Type of product (Family)	Accessories
Product name (Series)	Cable reductions
Number of wires/cables	1 single conductor
Colour	black
Dimension	Φ 16.0 mm (est.), Φ 8.5 mm (inner), 9.5 mm (thickness)

**i** Can be used only for connectors with outer cable 7.0 mm - 13.5 / 7.0 mm - 14.0 mm.

#### MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

#### CABLE CHARACTERISTICS

Cable diameter min. - max.	7.5 mm - 9.0 mm • Nut tightened 2.5 Nm.
Cable diameter with reduction	6.5 mm - 8.5 mm (with accessory code 6000087LF) • Nut tightened 2.5 Nm.

#### MATERIAL CHARACTERISTICS

Body	TPE
Material properties	Halogen Free - Silicone Free
Operating temperature range	-40°C / +125°C

#### PACKAGING INFORMATION

Packaging method	non assembled
Quantity (product/bag)	200 products/sacchetto
Unit weight	1.38 gram/product
Box dimension	-