



Seal, Mounting type: Plug in, Length x width: 20.3 mm, Max. cable diameter: 10 mm, IP 66, Colour: Black

#### **RAL:** 9005

#### **Business data**

Article number	28529.4
Article name	KDS-DE 9-10 BK
GTIN (EAN)	4044211210953
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5.3 g
Weight per piece (including packaging)	5.7 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Sealing Element
Colour	Black



### **Technical data**

Dimensions	
Length	20.3 mm
Width	20.3 mm
Height	17.7 mm
Materials	
Material	TPE
Flammability class UL 94	НВ
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Halogen-free	$\checkmark$
Silicone-free	$\checkmark$
UV-resistant	$\checkmark$
Further technical data	
Mounting type	Plug in
Degree of protection	IP66
Strain relief	$\checkmark$
Cable diameter, min.	9 mm
Cable diameter, max.	10 mm
NEMA Туре	1, 12, 4x (indoor use only)
Number of wires	1
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes



### Approvals

Standards and regulations				
Standards / specifications	Strain relief complying with DIN EN 62444			
cUL Recognized				
cUL approval	C22.2 No. 14-18			
cUL File Number	E489821			
cUL Recognized	1			
UL Recognized				
UL approval	UL 508A			
UL File Number	E489821			
UL Recognized	1			
UL Type Rating	1, 12, 4x (indoor use only)			
German Lloyd approval				
DNV GL Certificate number	TAE00003V7			
DNV GL Location Classes	Temperature: -40°C to 120°C, Humidity: B, Vibration: B, Ingress protection: IP66			
DNV GL approval granted	1			



### Media





#### Accessories

Inlays				
	Cable entry, In	lay, Mounting type: Plug in, IP 6	66, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28516.4	KDS-Inlay 1 BK	4044211210847	5 ST
	Cable entry, In	lay, Mounting type: Plug in, IP 6	66, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28517.4	KDS-Inlay 2 BK	4044211210854	5 ST
6	Cable entry, In	lay, Mounting type: Plug in, IP 6	66, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
Ŧ	28518.4	KDS-Inlay 4 BK	4044211210861	5 ST
11	Cable entry, In	lay, Mounting type: Plug in, IP 6	66, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28519.4	KDS-Inlay 6 BK	4044211210014	5 ST

#### **Screw frame**



Cable entry with foamed-in seal, Mounting type: Screws, Length: 153 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28504.4	KDS-SR 10/24 BK	4044211210809	1 ST



Cable entry with foamed-in seal, Mounting type: Screws, Length: 106 mm, Width: 70 mm, IP 66, Colour: Black

•	Article number	Article name	GTIN (EAN)	Packaging unit
	28500.4	KDS-SR 6/10 BK	4044211210021	1 ST



#### **Screw frame**



Cable entry with foamed-in seal, Mounting type: Screws, Length: 126 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28502.4	KDS-SR 8/16 BK	4044211210786	1 ST



Cable entry with foamed-in seal, Mounting type: Screws, Length: 81 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28506.4	KDS-SR 1-4 BK	4044211210823	1 ST

#### Locking frame

	Inner locking fr	ame, Length: 80 mm, Height: 1	1.5 mm, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	28507.4	KDS-IVR 1-4 BK	4044211210830	10 ST
	Inner locking fr	ame, Length: 105 mm, Height:	11.5 mm, Colour: Black	
	Article number	Article name	GTIN (EAN)	Packaging unit
	<u>28501.4</u>	KDS-IVR 6/10 BK	4044211210779	10 ST
		KDS-IVR 6/10 BK rame, Length: 125 mm, Height:		10 ST
				10 ST Packaging unit
•	Inner locking fr	ame, Length: 125 mm, Height:	11.5 mm, Colour: Black	Packaging
	Inner locking fr Article number 28503.4	ame, Length: 125 mm, Height: Article name	11.5 mm, Colour: Black GTIN (EAN) 4044211210793	Packaging unit
	Inner locking fr Article number 28503.4	rame, Length: 125 mm, Height: Article name KDS-IVR 8/16 BK	11.5 mm, Colour: Black GTIN (EAN) 4044211210793	Packaging unit

#### **Actuating tool**





Using the KDS BW1 actuating tool, the seals can be conveniently mounted in and dismantled from the frame. The ergonomic grip and the special shape enable simple and precise installations, especially for cabling applications in confined spaces., Material: Polyamide

Article number	Article name	GTIN (EAN)	Packaging unit
28622.0	KDS BW 1	4044211216597	1 ST