# **Data sheet** 28533.4 KDS-DE 13-14 BK





Seal, Mounting type: Plug in, Length x width: 20.3 mm, Max. cable diameter: 14 mm, IP 66, Colour: Black

**RAL:** 9005

#### **Business data**

Article number	<u>28533.4</u>
Article name	KDS-DE 13-14 BK
GTIN (EAN)	4044211210991
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	5 g
Weight per piece (including packaging)	5.4 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Sealing Element
Colour	Black





Technical data		
Dimensions		
Length	20.3 mm	
Width	20.3 mm	
Height	17.7 mm	
Materials		
Material	TPE	
Flammability class UL 94	НВ	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Halogen-free	✓	
Silicone-free	✓	
UV-resistant	✓	
Further technical data		
Mounting type	Plug in	
Degree of protection	IP66	
Strain relief	✓	
Cable diameter, min.	13 mm	
Cable diameter, max.	14 mm	
NEMA Type	1, 12, 4x (indoor use only)	
Number of wires	1	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

**UL Type Rating** 

German Lloyd approval

DNV GL Certificate number

**DNV GL Location Classes** 

DNV GL approval granted

28533.4 KDS-DE 13-14 BK





#### **Approvals** Standards and regulations Standards / specifications Strain relief complying with DIN EN 62444 **cUL** Recognized C22.2 No. 14-18 cUL approval cUL File Number E489821 cUL Recognized 1 **UL Recognized UL** approval **UL 508A UL File Number** E489821 **UL** Recognized 1

1, 12, 4x (indoor use only)

B, Ingress protection: IP66

Temperature: -40°C to 120°C, Humidity: B, Vibration:

TAE00003V7

1





#### Media







#### **Accessories**

#### Inlays

Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black



Article number	Article name	GTIN (EAN)	Packaging unit
<u>28516.4</u>	KDS-Inlay 1 BK	4044211210847	5 ST



Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28517.4	KDS-Inlay 2 BK	4044211210854	5 ST



Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28518.4	KDS-Inlay 4 BK	4044211210861	5 ST



Cable entry, Inlay, Mounting type: Plug in, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28519.4	KDS-Inlay 6 BK	4044211210014	5 ST

#### Screw frame



Cable entry with foamed-in seal, Mounting type: Screws, Length: 153 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28504.4	KDS-SR 10/24 BK	4044211210809	1 ST



Cable entry with foamed-in seal, Mounting type: Screws, Length: 106 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28500.4	KDS-SR 6/10 BK	4044211210021	1 ST





#### **Screw frame**



Cable entry with foamed-in seal, Mounting type: Screws, Length: 126 mm, Width: 70 mm, IP 66, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28502.4	KDS-SR 8/16 BK	4044211210786	1 ST



Cable entry with foamed-in seal, Mounting type: Screws, Length: 81 mm, Width: 70 mm, IP 66, Colour: Black


Article number	Article name	GTIN (EAN)	Packaging unit
28506.4	KDS-SR 1-4 BK	4044211210823	1 ST

#### **Locking frame**



Inner locking frame, Length: 80 mm, Height: 11.5 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28507.4	KDS-IVR 1-4 BK	4044211210830	10 ST



Inner locking frame, Length: 105 mm, Height: 11.5 mm, Colour: Black

Article number	Article name	GTIN (EAN)	unit
28501.4	KDS-IVR 6/10 BK	4044211210779	10 ST



Inner locking frame, Length: 125 mm, Height: 11.5 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28503.4</u>	KDS-IVR 8/16 BK	4044211210793	10 ST



Inner locking frame, Length: 152 mm, Height: 11.5 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28505.4	KDS-IVR 10/24 BK	4044211210816	10 ST

#### **Actuating tool**

# **Data sheet** 28533.4 KDS-DE 13-14 BK





Using the KDS BW1 actuating tool, the seals can be conveniently mounted in and dismantled from the frame. The ergonomic grip and the special shape enable simple and precise installations, especially for cabling applications in confined spaces., Material: Polyamide

Article number	Article name	GTIN (EAN)	Packaging unit
28622.0	KDS BW 1	4044211216597	1 ST