



THB.387.N5A

TH387 - mini-Plug&Socket connector IP66/IP68

MADE IN ITALY




IP68 IP66









INSTALLATION INSTRUCTIONS

- 606002031 TH387 parete v02 Lungo PDF • 474 KB
- IST TH387 parete v02 PDF • 691 KB
- Techno AssemblyTH387 PDF • 1 MB

CERTIFICATIONS AND TEST REPORTS

- 277 KB

GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP66/IP68 Plug&Socket circular connectors
Product name (Series)	TH387 - mini-Plug&Socket connector IP66/IP68
Product configuration	Panel-mounted plug connector with fixing nut <i>* Fixing nut included in the kit.</i>
Thread	M20
Panel thickness min. - max.	1.0 mm - 9.0 mm
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 23 mm x (61 ÷ 76 mm) (when plug-socket matched)


ELECTRICAL CHARACTERISTICS

Number of poles	5
Contact marking	1 - 2 - 3 - 4(E) - 5
Type of connection	screw (M2 - max. 0.2 Nm)
Operating current	max. 17.5A (EN61984) - max. 15A (UL2238/C22.2 No. 182.3)
Operating voltage	max. 450V (EN61984) - max. 400V (UL2238/C22.2 No. 182.3)
Impulse withstand voltage	4KV

 Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP66/IP68 (30m,3h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

 Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.25 mm ² - 1.5 mm ²
Wire cross-section min. - max. (Solid cable)	0.25 mm ² - 1.5 mm ²

MATERIAL CHARACTERISTICS

Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	TPE-S
Grommets	TPE-S
Contacts	CuZn (silver plated)
Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free - Silicone Free
T marking	T 125°C



Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

i Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009
-----------------	---------------

PACKAGING INFORMATION

Packaging method	not assembled components
Quantity (product/box)	200 products/box
Unit weight	15,1 gram/product
Box dimension	300 x 200 x 160