



Cable reductions

















## **GENERAL DESCRIPTION**

| Type of product (Family)   | Accessories                               |  |
|--|---|--|
| Product name (Series)  | Cable reductions                          |  |
| Number of wires/cables   | flat cable                                |  |
| Colour   | Techno green                              |  |
| Dimension  | $\Phi$ 16.0 mm (est.), 9.5 mm (thickness) |  |
| Can be used only for connectors with outer cable 7.0 mm - 13.5 / 7.0 mm - 14.0 mm. |   |  |

**MECHANICAL CHARACTERISTICS** 

| Protection against solid/water (IP) | IP68  |
|-------------------------------------|---|
| Corrosion resistance                | Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h) |

## **CABLE CHARACTERISTICS**

| Cable diameter min max. | 5.5 mm x 11.0 mm                   |
|-------------------------|------------------------------------|
|                         | Cavo piatto. Nut tightened 2.5 Nm. |

## MATERIAL CHARACTERISTICS

| Body                        | TPE                          |
|-----------------------------|------------------------------|
| Material properties         | Halogen Free - Silicone Free |
| Operating temperature range | -40°C/+125°C                 |

## **PACKAGING INFORMATION**

| Packaging method       | non assembled          |
|------------------------|------------------------|
| Quantity (product/bag) | 200 products/sacchetto |
| Unit weight            | 1.48 gram/product      |
| Box dimension          | -                      |