

ZR 011 Dual Thermostat

IP20




- NO and NC in one casing
- High switching capacity
- Clip Fixing
- Separate adjustable temperatures
- Terminals easily accessible

Two thermostats in one casing:


Thermostat(contact breaker, normally closed)for regulating heaters Thermostat(contact make, normally open) for regulating filter fans and heat exchangers or switching signal devices when temperature limit has been exceeded.

Heaters and cooling equipment can be switched independently from each other with a temperature offset a he usual change-over contacts.

Dimensions



ZR 011(NC/NO)



Temperature range	NO/NC:0-+60 C
Switch temperature difference	7K(+4K tolerance)
Sensor element	thermostatic bimetal
Contact type	Snap-action
Contact resistance	< 10m ohm
Service life	>100,000 cycles
Max. Switching capacity	250VAC,10(2)A, 120VAC,15(2)A, DC 30W
Connection	4-pole terminal, clamping torque 0.5Nm max.: rigid wire 2.5mm ² , stranded wire (with wire end ferrule) 1.5mm ²
Installation	35mm DIN Installation guide
Casing	UL94 V-0 Plastic, light gray
Dimensions	67×50×46mm
Weight	90g
fitting position	variable
Operating/Storage temperature	-20~+80 C
Protection type	IP20

Setting range	Art. No. Contact Maker (NC/NO)	Approvals
0 to +60°C	ZR 011	CE