



Cable entry with membrane for unassembled cables, Mounting type: Snap-in, Length: 142 mm, Width: 44 mm, IP64, Colour: Grey

**RAL:** Ähnlich 7035

### Business data

Article number	28818.6
Article name	KES-E 50/24 A GR
GTIN (EAN)	4044211234171
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	46.1 g
Weight per piece (including packaging)	46.98 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Cable Entry
Colour	Grey

### Technical data

#### Dimensions

Length	142 mm
Length of wall cutout	112 mm
Width	44 mm
Width of wall cutout	36 mm
Height	12 mm
Installation height	5 mm

#### Materials

Material	TPE
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	90 °C
Sealing material	TPE
Halogen-free	✓
Silicone-free	✓

#### Further technical data

Mounting type	Snap-on
Degree of protection	IP54
Sheet thickness min.	1.5 mm
Sheet thickness max.	2.5 mm
NEMA Type	1, 12
Number of wires	50
Number of cables for cable diameters 1.0 - 5.3 mm	33
Number of cables for cable diameters 1.0 - 6.4 mm	9
Number of cables for cable diameters 1.0 - 8.3 mm	8

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Approvals

---

#### cUL Recognized

cUL approval	C22.2 No. 14-18
cUL File Number	E489821
cUL Recognized	1

#### UL Recognized

UL approval	UL 508A
UL File Number	E489821
UL Recognized	1
UL Type Rating	1, 12

# Data sheet

28818.6 KES-E 50/24 A GR

---

## Media

---



---

### Accessories

---