



Multifunction timing relay module, Interface Relay Compact (IRC) complete, Consisting of base MFR-IRCP with Screw connection and Plug-in miniature relay PRC with power contact, Mounting type: TS 35, 1 Changeover contact, Input voltage: 12 VAC / DC

#### **Business data**

Article number	16256.2
Article name	MFR IRCPU 1/24V AC/DC
GTIN (EAN)	4044211200381
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	43 g
Weight per piece (including packaging)	44 g
Unit of weight	G
Customs number	85364900
Country of origin	DE
Product description	Complete module
-	



## 16256.2 MFR IRCPU 1/24V AC/DC

Technical data	
Dimensions	
Length	94.3 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	95.4 mm
Ratings	
Rated voltage	250 V
Rated frequency min.	50 Hz
Rated frequency max.	60 Hz
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Stripping length	10 mm
Torque	0.5 Nm
Input data	
Holding current	0,6 Un -
Drop-out voltage	0.1 Un
Power supply AC/DC	24 V
Control pulse length, min.	50 ms
Power consumption	0,3 W
Tolerance	(0,8 - 1,1) Un
Power-on duration	50 ms
Recovery time	<50 ms



### 16256.2 MFR IRCPU 1/24V AC/DC

Technical data		
Output data		
Switching voltage, max.		400
Continuous current max. / In	rush current max.	6 / 10 A
Switching capacity, max.		1500 VA
Electrical lifespan (AC1)		60x10 <sup>3</sup>
Mechanical lifespan		10×10 <sup>6</sup>
Contact load, min.		500 mW
Relay contact		1 CO contact
Materials		
Contact material		AgNi
Working temperature, min.		-40 °C
Working temperature, max.		50 °C
Time functions		
Time range		0,1 s - 6 h
Setting ranges		4
Accuracy		
Setting tolerance		± 5%
Repeat accuracy		± 1%
Control contact		
Input	Voltage applied, te	erminals A1-B1
Response threshold	Automatically adju	isted to supply voltage
Further technical data		
Status display		✓
Storage temperature, min.		-25 °C
Storage temperature, max.		70 °C
Environmental Product Co	mpliance	
REACH Conform	-	yes
REACH Reference date		2023-06-14
REACH Candidate Substance	ce Note	No
RoHS Conform		yes




### 16256.2 MFR IRCPU 1/24V AC/DC

Approvals		
Standards and regulations		
CE compliant	yes	



16256.2 MFR IRCPU 1/24V AC/DC

### Media







#### **Accessories**

#### Relays



Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15502.2</u>	PRC 1/24V DC	4044211118143	10 ST

#### **Adapter**



Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST

#### **Fuse modules**



Interface-Relay-Compact (IRC) fuse module to combine with IRCP, FIRCP, MFR-IRCP and MFR-FIRCP relays and socket bases, for holding 5x20 fuse, Voltage: 250 V, Current: 6 A

Article number	Article name	GTIN (EAN)	Packaging unit
16208.2	SM-IRC	4044211187637	10 ST

#### **Cross-connector**

External cross-connector insulated for Interface-Relay-Compact (IRC), 16-pole, can be shortened, Voltage: 250 V, Current: 6 A



Article number	Article name	GTIN (EAN)	Packaging unit
<u>16209.4</u>	AQI/IRC/16 BK	4044211187651	10





#### **Partition plate**



Partition plate for Interface-Relay-Compact (IRC) for separating relay blocks, variable width: 1.5 or 6.2 mm

Article number	Article name	GTIN (EAN)	Packaging unit
16228.2	TW/IRC	4044211187675	10 ST

#### **Quick marking**



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article number Article name		Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST

#### **Screwdriver**

Screwdriver with bare blade, Colour: Black-grey

#CONTACLE	Article number	Article name	GTIN (EAN)	Packaging unit
	1086.0	SDB 0,6x3,5	4044211014797	1 ST