

## CLIPPER FOOTSWITCH



Clipper Footswitch



Clipper Wide Treadle Footswitch

### Environmental Ratings:

EN 60529 Degree of Protection IP20

### Key Benefits

The rugged, long life Clipper foot switch models have proved themselves in the field over many years of usage. All maintained models offer "Push On-Push Off" action that insures long trouble-free performance. The wide treadle models offer a large seven inch target for the operator's foot. Cast iron housing. Nonskid base pad. Complete with adjustable strain relief connector. Black finish.

Size: 4-1/2" x 3-1/2" x 1-1/2"  
Weight: 2-1/4 lbs.

The CLIPPER TWIN consists of two SPDT or two DPDT foot switches mounted on a heavy steel base plate with nonskid pad. Divider bar between pedals helps prevent accidental operation of both pedals at one time. A tube between the two foot switches conceals all internal wiring between them. A conduit opening with strain relief connector is provided in the right foot switch.

Size: 8-3/8" x 4-1/2" x 1-1/2"  
Weight: 5 lbs.

Model 638-S features a cast aluminum housing painted Alert Orange with a splash resistant interior switch.

[Request A Quote](#)

### SPECIFICATIONS

(Special variations are available to the O.E.M. on special order on the models listed below)

**⚠ WARNING**

CATALOG NUMBER		DESCRIPTION	CIRCUIT	FORM	ELECTRICAL RATINGS
REGULAR TREADLE	WIDE TREADLE				
632-S	642-S	Momentary	SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC
632-SC3*		Momentary	SPST Wired N.O.	A	15 A 125 VAC 3/4 H.P. 125 VAC
633-S	643-S	Momentary	SPDT DB±	Z	20 A 125-250 VAC 3/4 H.P. 125 VAC 1 H.P. 250 VAC
635-S	645-S	Momentary	DPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
636-S	646-S	Two Stage Momentary	Each Stage SPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
632-DA	642-DA	Maintained	SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC

	634-DA		Maintained	DPDT	C	10 A 125-250 VAC 1/8 H.P. 125 VAC 1/4 H.P. 250 VAC
	<b>TWIN 632-S</b>		Momentary	Each Side SPDT	C	20 A 125-250 VAC 1 H.P. 125-250 VAC
	TWIN 635-S		Momentary	Each Side DPDT	C	15 A 125 VAC 10 A 250 VAC 1/2 H.P. 125-250 VAC
	638-S		Momentary	SPDT	C	10 A 125-250 VAC 1/2 H.P. 125-250 VAC
	638-SC38** (IP21)		Momentary	SPST Wired N.O.	A	10 A 125-250 VAC 1/2 H.P. 125-250 VAC

**Model 638-S features a cast aluminum housing painted Alert Orange with a splash resistant interior switch.**

**\*Supplied with 8 ft. 14/3 cord and 3 prong series plug. Green lead grounded.**

**\*\*Supplied with 8 ft. 16/3 cord, wired N.O. with green lead grounded.**

**±DB Double Break models must be wired to equal voltage sources and the same polarity. The loads should be on the same sides of the line.**

**BOLD COPY INDICATES STOCK ITEM**

[Home](#) | [About](#) | [Products](#) | [Catalog](#) | [Int'l Distributors](#) | [Glossary](#) | [Support](#) | [Representative](#) | [ISO-9001](#) | [Literature](#) | [Press](#) | [Shows](#) | [Directions](#) | [Contact](#)

LINEMASTER Switch Corporation · 29 Plaine Hill Road · POB 238 · Woodstock, CT 06281-0238 · USA

Tel: 860.974.1000 Fax: 860.974.0691 or Toll-Free Fax 800.974.3668 (USA Only)

© Copyright  
Linemaster Switch Corporation  
2005