

# LARGE TRIM SWITCHES, 4 & 5-WAY

## 4-WAY TOGGLE SWITCHES WITH OR WITHOUT CENTER PUSHBUTTON

### T4-0010

**Actuation:** Center position maintained, all other positions momentary  
**Rating:** 5 amps Resistive @ 30VDC sea level  
 3 amps Inductive @ 30VDC sea level  
 DWV: 1050Vrms @ sea level  
 400Vrms @ 70,000 feet  
**Electrical Life:** 100,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black thermoplastic  
**Case:** Black anodized aluminum alloy



### T5-0004

**Actuation:** Toggle & Pushbutton: center position maintained, all other positions momentary  
**Rating:** 2 amps Resistive @ 28VDC or 115VAC/60Hz  
 DWV: 1050Vrms  
**Electrical Life:** 50,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T4-0065

**Actuation:** Center position maintained, all other positions momentary  
**Rating:** 5 amps Resistive @ 30VDC sea level  
 2.5 amps Resistive @ 70,000 feet  
 3 amps Inductive @ 30VDC sea level  
 1.5 amps Inductive @ 70,000 feet  
 DWV: 1050Vrms @ sea level  
 400Vrms @ 70,000 feet  
**Electrical Life:** 100,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black nylon  
**Case:** Black anodized aluminum alloy



### T5-0015

**Actuation:** Toggle & Pushbutton: center position maintained, all other positions momentary  
**Rating:** 2 amps Resistive @ 28VDC or 115VAC/60Hz  
 DWV: 1050Vrms  
**Electrical Life:** 50,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Gray thermoplastic



### T4-0082

**Actuation:** Toggle: center position maintained, all other positions momentary  
**Rating:** 5 amps Resistive @ 30VDC sea level  
 3 amps Inductive @ 30VDC sea level  
 DWV: 1050Vrms @ sea level  
**Electrical Life:** 50,000 cycles  
**Enclosure:** Resilient per MIL-PRF-8805 Design 4  
**Button:** Black nylon  
**Case:** Aluminum alloy



### T5-0018

**Actuation:** Toggle & Pushbutton: center position maintained, all other positions momentary  
**Rating:** 2 amps Resistive @ 28VDC or 115VAC/60Hz  
 DWV: 1050Vrms  
**Electrical Life:** 50,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black thermoplastic  
**Case:** Black anodized aluminum alloy



### T4-0111

**Actuation:** Toggle: center position maintained, all other positions momentary  
**Rating:** 2 amps Resistive @ 28 VDC sea level  
 .5 amps Inductive @ 28 VDC sea level  
 DWV: 1050Vrms @ sea level  
**Electrical Life:** 100,000 cycles, each direction  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black Nylon  
**Case:** Black anodized aluminum alloy



### T5-0028

**Actuation:** Toggle & Pushbutton: center position maintained, all other positions momentary  
**Rating:** 2 amps Resistive @ 28VDC or 115VAC/60Hz  
 DWV: 1050Vrms  
**Electrical Life:** 50,000 cycles  
**Enclosure:** Dusttight per MIL-PRF-8805 Design 2  
**Button:** Black thermoplastic  
**Case:** Black anodized aluminum alloy



NOTE: Contact factory for additional configurations.