

MM-EMLF (EX12)R C1 YE/BK - Label, highly flexible



0803942

<https://www.phoenixcontact.com/au/products/0803942>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Label, highly flexible, Roll, yellow/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, text field height: 10 mm, text field width: 8000 mm

Your advantages

- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing
- The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- The material is cUL certified

Commercial data

| | |
|--------------------------------------|--------------------|
| Item number | 0803942 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BG241E |
| Product key | BG241E |
| Catalog page | Page 48 (C-3-2019) |
| GTIN | 4055626212210 |
| Weight per piece (including packing) | 60.2 g |
| Weight per piece (excluding packing) | 60.6 g |
| Customs tariff number | 96121010 |
| Country of origin | CN |

MM-EMLF (EX12)R C1 YE/BK - Label, highly flexible



0803942

<https://www.phoenixcontact.com/au/products/0803942>

Technical data

Product properties

| | |
|------------------|-----------------|
| Product type | Device marking |
| Product property | Highly flexible |

Marking

| | |
|---------------------------|------------------|
| Identification technology | Thermal transfer |
|---------------------------|------------------|

Mounting

| | |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

Material specifications

| | |
|---------------|--------------------------------|
| Foil strength | 70 µm |
| Adhesive | Acrylic |
| Color | multicolored |
| | yellow (RAL 1018) |
| | black (RAL 9005) |
| Material | Vinyl polymer |
| Components | Free from silicone and cadmium |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

| | |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |

Wipe resistance of inscriptions

| | |
|---|--|
| Specification | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl [CAS No. 67-63-0] | Test passed |
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide

| | |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |

MM-EMLF (EX12)R C1 YE/BK - Label, highly flexible



0803942

<https://www.phoenixcontact.com/au/products/0803942>

Salt spray test

| | |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 75 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % (Storage in a dry and dark place in the original packaging is recommended) |
| Shelf life | 2 years |

Dimensions

| | |
|--------|-------|
| Height | 12 mm |
| Length | 8 m |

Text field

| | |
|-------------------|---------|
| Text field width | 8000 mm |
| Text field height | 10 mm |

Standards and regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

MM-EMLF (EX12)R C1 YE/BK - Label, highly flexible



0803942

<https://www.phoenixcontact.com/au/products/0803942>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/0803942>



cULus Recognized

Approval ID: MH48542

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27281103 |
|-------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001288 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |