


# US-WMTB (24X5) YE - Cable marker



0828958  
<https://www.phoenixcontact.com/au/products/0828958>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker, Card, yellow, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, THERMOMARK PRIME 2.0, mounting type: Assembly with cable ties, cable diameter: > 13 mm, Number of individual labels: 35, text field height: 5 mm, text field width: 24 mm

## Your advantages

- The markers, which are supplied as uniform cards, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- The US-WMTB... UniSheet labeling range includes markers that can be secured using standard cable binders
- The perforated marking strips are easy to separate and can be easily fitted
- The cards provide space for including function texts

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0828958             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BG2319              |
| Product key                          | BG2319              |
| Catalog page                         | Page 214 (C-3-2019) |
| GTIN                                 | 4046356559881       |
| Weight per piece (including packing) | 12.372 g            |
| Weight per piece (excluding packing) | 12.372 g            |
| Customs tariff number                | 39204910            |
| Country of origin                    | DE                  |

# US-WMTB (24X5) YE - Cable marker



0828958

<https://www.phoenixcontact.com/au/products/0828958>

## Technical data

### Product properties

|              |                   |
|--------------|-------------------|
| Product type | Conductor marking |
| Type         | Card form         |

### Marking

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Number of individual labels         | 35                                    |
| Number of individual labels per row | 7                                     |
| Identification technology           | Thermal transfer for sheets and cards |

### Dimensions

|        |       |
|--------|-------|
| Width  | 14 mm |
| Length | 24 mm |

### External dimensions

|                  |                    |
|------------------|--------------------|
| Outside diameter | > 13 mm ... 136 mm |
|------------------|--------------------|

### Text field

|                   |       |
|-------------------|-------|
| Text field width  | 24 mm |
| Text field height | 5 mm  |

### Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Color                                  | yellow (RAL 1018) |
| Material                               | PVC               |
| Flammability rating according to UL 94 | V0                |
| Components                             | Silicone-free     |

### Cable/line

|                         |            |
|-------------------------|------------|
| External cable diameter | > 13.00 mm |
|-------------------------|------------|

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

#### UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result        | Test passed                    |
| Test duration | 96 h                           |

#### Wipe resistance of inscriptions

|                                |                                                |
|--------------------------------|------------------------------------------------|
| Specification                  | DIN EN 61010-1 (VDE 0411-1):2011-07            |
|                                | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl<br>[CAS No. 67-63-0] | Test passed                                    |

# US-WMTB (24X5) YE - Cable marker



0828958

<https://www.phoenixcontact.com/au/products/0828958>

|                                                 |             |
|-------------------------------------------------|-------------|
| n-Hexane<br>[CAS No. 110-54-3]                  | Test passed |
| Water + Petroleum ether<br>[CAS No. 64742-82-1] | Test passed |

## Testing in a condensation changing climate in the presence of sulfur dioxide

|               |                   |
|---------------|-------------------|
| Specification | DIN 50018:2013-05 |
| Result        | Test passed       |
| Climate level | AHT 1.0 S         |
| Cycles        | 2                 |

## Salt spray test

|               |                           |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result        | Test passed               |

## Ambient conditions

|                                                     |                                                                                                         |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)                     | -30 °C ... 80 °C                                                                                        |
| Recommended storage conditions                      | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |
| Recommended ambient temperature (storage/transport) | 23 °C                                                                                                   |
| Recommended humidity (storage/transport)            | 50 %                                                                                                    |
| Shelf life                                          | 12 months                                                                                               |

## Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

## Mounting

|               |                          |
|---------------|--------------------------|
| Mounting type | Assembly with cable ties |
|---------------|--------------------------|

# US-WMTB (24X5) YE - Cable marker



0828958

<https://www.phoenixcontact.com/au/products/0828958>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281102 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

# US-WMTB (24X5) YE - Cable marker



0828958  
<https://www.phoenixcontact.com/au/products/0828958>

## Environmental product compliance

|                                         |                            |
|-----------------------------------------|----------------------------|
| EU RoHS                                 |                            |
| Fulfills EU RoHS substance requirements | Yes, No exemptions         |
| EU REACH SVHC                           |                            |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt% |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)