

https://www.phoenixcontact.com/au/products/1040620



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in bridge, pitch: 10.2 mm, number of positions: 5, color: blue

Commercial data

Item number	1040620
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE2Z2X
Product key	BE2Z2X
GTIN	4055626597331
Weight per piece (including packing)	18.38 g
Weight per piece (excluding packing)	18.2 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/au/products/1040620



Technical data

Product properties

Product type	Plug-in bridge
Number of positions	5
Pitch	10.2 mm

Electrical properties

Maximum load current	57 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Connection data

Maximum load current	57 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Dimensions

Pitch 10.2 mm	
---------------	--

Material specifications

Color	blue (RAL 5015)
Material	Copper
Flammability rating according to UL 94	VO
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (operation)	20 % 90 %
Permissible humidity (storage/transport)	30 % 70 %

Mounting

Mounting type	Plug-in mounting
---------------	------------------



https://www.phoenixcontact.com/au/products/1040620



Classifications

UNSPSC 21.0

_	\sim	$\Lambda \cap \cap$
		A.7.7

	ECLASS-13.0	27250303
ΕΊ	ТМ	
	ETIM 9.0	EC000489
U	ISPSC	

39121400



https://www.phoenixcontact.com/au/products/1040620



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au