

1100077

https://www.phoenixcontact.com/au/products/1100077

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail adapter, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: PC-GF10, connection method: IDC connection, connection cross section: AWG 26- 22, Item set, DIN rail adapter including RJ45 cable connection module

Product description

Compact DIN rail adapter, including RJ45 cable connection module, with optional shield connection, with dust protection cover, one-piece design

Your advantages

- · Compact design
- · For distributing copper and fiber optic cabling
- · Front release without special tool
- One-Piece Design
- · Assembly without special tools
- · Optional overall shielding braid for copper modules
- · Security elements available as accessories
- · Adapter-less integration of module inserts
- Marking service: Phoenix Contact can custom-mark all labels according to your requirements

Commercial data

Item number	1100077
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABNLAA
Product key	ABNLAA
GTIN	4055626951447
Weight per piece (including packing)	49 g
Weight per piece (excluding packing)	49 g
Customs tariff number	85366990
Country of origin	DE



1100077

https://www.phoenixcontact.com/au/products/1100077

Set consists of

NBC-PP-G1PGY - DIN rail adapter

1041740

https://www.phoenixcontact.com/au/products/1041740



DIN rail adapter, design: Headers with shielding, degree of protection: IP20, material: PC-GF10, connection method: Quick connection, without assembled modules

CUC-I-J1ZNI-S/R4IDC8 - RJ45 jack insert

1417274

https://www.phoenixcontact.com/au/products/1417274



RJ45 jack insert, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: IDC connection, connection cross section: AWG 26- 22, cable outlet: straight, Adapter-free design, Ethernet



1100077

https://www.phoenixcontact.com/au/products/1100077

Technical data

Notes

Product properties		
	Product type	Patch panel
	Туре	RJ45
	Number of positions	8

Set item with RJ45 cable connection module

Electrical properties

Number of slots

Notes on operation

Rated voltage (III/3)	72 V (DC)
Frequency range	500 MHz
Contact resistance	≤ 5 mΩ (Shield-ground, optional)
Transmission medium	Copper

Connection data

Dimensions

Width	18 mm
Height	80 mm
Depth	64.6 mm

Material specifications

Flammability rating according to UL 94	V0
Housing material	PC-GF10
Material, protective cover	PC

Cable/line

External cable diameter	4.5 mm 9 mm	

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-10 °C 60 °C
Ambient temperature (storage/transport)	-40 °C 60 °C

Mounting

Mounting type	DIN rail mounting



1100077

https://www.phoenixcontact.com/au/products/1100077

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/1100077



EAC

Approval ID: 19060508



1100077

https://www.phoenixcontact.com/au/products/1100077

Classifications

_	\sim	$\Lambda \cap \cap$
		A.7.7

	ECLASS-13.0	27440392	
Εī	ETIM		
	ETIM 9.0	EC002943	
UNSPSC			
	UNSPSC 21.0	39121400	



1100077

https://www.phoenixcontact.com/au/products/1100077

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au