

1209091

https://www.phoenixcontact.com/au/products/1209091

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Voltage tester, for DC and AC voltages from 12 V to 1000 V AC/1000 V DC, IP65

Your advantages

- DC and AC voltage tests in the range from 12 V to 1000 V AC/DC, fully functional even without batteries
- Polarity test (+/-) for DC voltage
- · Single-pos. test of the phase conductor
- · Indicator for the direction of rotating field of a three-phase network as long as the star point is grounded
- · Measuring point lighting
- · Load connection via pushbutton
- Overvoltage category CAT IV 600 V and CAT III 1000 V in accordance with IEC/EN 61243-3
- Vibration alarm for safe voltage detection
- Shock-proof, dust-proof, and splash-proof housing, IP65
- · Audible and optical continuity test

Commercial data

Item number	1209091
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH3312
Product key	BH3312
Catalog page	Page 463 (C-3-2019)
GTIN	4046356309905
Weight per piece (including packing)	367 g
Weight per piece (excluding packing)	318.3 g
Customs tariff number	90303370
Country of origin	IE



https://www.phoenixcontact.com/au/products/1209091



Technical data

Notes

F - 1	Decided at	0 1'	
Environmental	Product	Compliance	

California Proposition 65	Further information on California's prop. 65 is available under
	"Downloads" in the manufacturer's declaration

Product properties

Product type	Measuring tools
Display scope	12 V, 24 V, 50 V, 120 V, 230 V, 400 V, 690 V, 1000 V LED diode display
Phase-sequence indicator	LCD (symbol "R")
Measuring point lighting	LED
Phase display	LCD (symbol "R")
Polarity display	LED (symbol "+/-")

Electrical properties

Innenwiderstand_Messkreis	220 kΩ
Innenwiderstand_Lastkreis	3.7 kΩ
Measuring category	CAT IV 600 V / CAT III 1000V
Power supply	2 x micro battery 1.5 V, LR03, AAA

Input data

Input voltage range AC	12 V AC 1000 V AC
Input voltage range DC	12 V DC 1000 V DC

Dimensions

Blade width	0 mm
Length	260 mm

Material specifications

Color	black

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-10 °C 55 °C

Standards and regulations



1209091

https://www.phoenixcontact.com/au/products/1209091

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/1209091



VDE approval of drawings Approval ID: 40038336



1209091

https://www.phoenixcontact.com/au/products/1209091

Classifications

_		
	വ	ΛCC
-		A.7.7

	ECLASS-13.0	27200308		
E ⁻	ГІМ			
	ETIM 9.0	EC002781		
UNSPSC				
	UNSPSC 21.0	41113600		



https://www.phoenixcontact.com/au/products/1209091



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au