

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protective device consisting of base element with Push-in connection technology and protective plugs, for mounting on NS 35/7.5. Nominal voltage: 230 V AC, 3+1 circuit

Your advantages

- Push-in connection technology for easy installation and uniform connection technology in the entire control cabinet
- Time savings when wiring thanks to not having to check the recommended connection torque
- Savings on additional installation materials thanks to through-wiring

Commercial data

Item number	1248961
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL132A
Product key	CL132A
GTIN	4063151353308
Weight per piece (including packing)	359.9 g
Weight per piece (excluding packing)	360.1 g
Customs tariff number	85363030
Country of origin	DE

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

Technical data

Product properties

Product type	Surge arrester
Product family	VALVETRAB MS
IEC test classification	II
	T2
EN type	T2
IEC power supply system	TN-S
	TT
Type	DIN rail module, two-section, divisible
Number of positions	4
Surge protection fault message	optical

Insulation characteristics

Overvoltage category	III
Pollution degree	2


Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)
-------------------------	---------------

Connection data

Connection method	Push-in connection
Stripping length	10 mm ... 12 mm
Conductor cross section rigid	0.5 mm ² ... 10 mm ²
Conductor cross section AWG	20 ... 8
Conductor cross section, flexible, with ferrule, with plastic sleeve	0.5 mm ² ... 6 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve	0.5 mm ² ... 10 mm ²

Dimensions

Dimensional drawing	
Width	71.2 mm
Height	89.8 mm
Depth	65.7 mm (incl. DIN rail 7.5 mm)
Horizontal pitch	4 Div.

Material specifications

Color (Base element)	gray (RAL 7042)
Color (Male connector)	light gray (RAL 7035)
Flammability rating according to UL 94	V-0

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

CTI value of material	600
Insulating material	PA 6.6/PBT
Material group	I
Housing material	PA 6.6
	PBT

Protective circuit

Mode of protection	L-N
	L-PE
	N-PE
Direction of action	3L-N & N-PE
Nominal voltage U_N	240/415 V AC (TN-S)
	240/415 V AC (TT)
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous operating voltage U_C (L-N)	275 V AC
Maximum continuous operating voltage U_C (L-PE)	275 V AC
Maximum continuous operating voltage U_C (N-PE)	260 V AC
Rated load current I_L	32 A (at 6 mm ²)
	40 A (at 10 mm ²)
Protective conductor current I_{PE}	≤ 5 μA
Standby power consumption P_C	≤ 360 mVA
Nominal discharge current I_n (8/20) μs	20 kA
Maximum discharge current I_{max} (8/20) μs	40 kA
Follow current interrupt rating I_{fi} (N-PE)	100 A
Short-circuit current rating I_{SCCR}	25 kA
Voltage protection level U_p (L-N)	≤ 1.35 kV
Voltage protection level U_p (L-PE)	≤ 1.6 kV
Voltage protection level U_p (N-PE)	≤ 1.5 kV
Residual voltage U_{res} (L-N)	≤ 1.35 kV (at I_n)
	≤ 1.1 kV (at 10 kA)
	≤ 1 kV (at 5 kA)
	≤ 0.9 kV (at 3 kA)
Residual voltage U_{res} (L-PE)	≤ 1.6 kV (at I_n)
	≤ 1.2 kV (at 10 kA)
	≤ 1 kV (at 5 kA)
	≤ 0.9 kV (at 3 kA)
Residual voltage U_{res} (N-PE)	≤ 0.4 kV (at I_n)
	≤ 0.25 kV (at 10 kA)
	≤ 0.15 kV (at 5 kA)
	≤ 0.1 kV (at 3 kA)
TOV behavior at U_T (L-N)	335 V AC (5 s / withstand mode)
	440 V AC (120 min / safe failure mode)
TOV behavior at U_T (N-PE)	1200 V AC (200 ms / withstand mode)
Response time t_A (L-N)	≤ 25 ns

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

Response time t_A (L-PE)	≤ 100 ns
Response time t_A (N-PE)	≤ 100 ns
Max. backup fuse with V-type through wiring	32 A (gG - 6 mm ²)
	35 A (gG - 10 mm ²)
	40 A (MCB C - 10 mm ²)
Max. backup fuse with branch wiring	125 A (gG)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (only when all terminal points are used)
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	25g (Half-sine / 11 ms / 3x $\pm X$, $\pm Y$, $\pm Z$)
Vibration (operation)	2g (10 ... 500 Hz / 2.5 h / X, Y, Z)

Standards and regulations

Standards/specifications	IEC 61643-11
Note	2011
Standards/specifications	EN 61643-11
Note	2012

Mounting

Mounting type	DIN rail: 35 mm
---------------	-----------------


VAL-MS 230/3+1-PT - Type 2 surge arrester

1248961


<https://www.phoenixcontact.com/au/products/1248961>

Drawings

Dimensional drawing



Diagram




VAL-MS 230/3+1-PT - Type 2 surge arrester

1248961

<https://www.phoenixcontact.com/au/products/1248961>

Circuit diagram



VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/1248961>



IECEE CB Scheme

Approval ID: NL-71987

CCA

Approval ID: NTR-NL 7875



KEMA-KEUR

Approval ID: 71-118125

UAE-RoHS

Approval ID: 22-09-51250

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961

<https://www.phoenixcontact.com/au/products/1248961>

Classifications

ECLASS

ECLASS-13.0	27171202
-------------	----------

ETIM

ETIM 9.0	EC000941
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

VAL-MS 230/3+1-PT - Type 2 surge arrester



1248961
<https://www.phoenixcontact.com/au/products/1248961>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au