


# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 500 V, nominal current: 24 A, connection method: Screw connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

## Your advantages

- Two connection points on each side to accommodate several conductors
- Double bridge shaft enables individual potential distribution and supply

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2775375             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE1213              |
| Product key                          | BE1213              |
| Catalog page                         | Page 470 (C-1-2019) |
| GTIN                                 | 4017918068578       |
| Weight per piece (including packing) | 12.76 g             |
| Weight per piece (excluding packing) | 11.58 g             |
| Customs tariff number                | 85369010            |
| Country of origin                    | CN                  |

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Technical data

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Product family        | UDK                            |
| Number of connections | 4                              |
| Number of rows        | 2                              |
| Potentials            | 1                              |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 6 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                                                           |                                                                                                                                                                |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of connections per level                                                           | 4                                                                                                                                                              |
| Nominal cross section                                                                     | 2.5 mm <sup>2</sup>                                                                                                                                            |
| Screw thread                                                                              | M3                                                                                                                                                             |
| Tightening torque                                                                         | 0.5 ... 0.6 Nm                                                                                                                                                 |
| Stripping length                                                                          | 8 mm                                                                                                                                                           |
| Internal cylindrical gage                                                                 | A3                                                                                                                                                             |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                                                                                                                                  |
| Conductor cross section rigid                                                             | 0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>                                                                                                                      |
| Cross section AWG                                                                         | 24 ... 12 (converted acc. to IEC)                                                                                                                              |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                    |
| Conductor cross section, flexible [AWG]                                                   | 24 ... 14 (converted acc. to IEC)                                                                                                                              |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.25 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                                                                                                                   |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                   |
| Cross-section with insertion bridge, rigid                                                | 2.5 mm <sup>2</sup>                                                                                                                                            |
| Cross-section with insertion bridge, flexible                                             | 2.5 mm <sup>2</sup>                                                                                                                                            |
| 2 conductors with same cross section, solid                                               | 0.2 mm <sup>2</sup> ... 1 mm <sup>2</sup>                                                                                                                      |
| 2 conductors with same cross section, flexible                                            | 0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                    |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                                                                                   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup>                                                                                                                      |
| Nominal current                                                                           | 24 A (with 4 mm <sup>2</sup> conductor cross section)                                                                                                          |
| Maximum load current                                                                      | 32 A (in case of a 4 mm <sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal voltage                                                                           | 500 V                                                                                                                                                          |
| Nominal cross section                                                                     | 2.5 mm <sup>2</sup>                                                                                                                                            |

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 5.2 mm  |
| End cover width    | 1.5 mm  |
| Height             | 63.5 mm |
| Depth on NS 32     | 52 mm   |
| Depth on NS 35/7,5 | 47 mm   |
| Depth on NS 35/15  | 54.5 mm |

## Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group                                        | I               |
| Insulating material                                              | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

## Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

## Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 (+/- 2) rpm               |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |
|               | NS 32     |

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Drawings

Circuit diagram



# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2775375>

|                                                                                                                    |                       |                       |                   |                             |
|--------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>CSA</b><br>Approval ID: 13631 |                       |                       |                   |                             |
|                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                        |                       |                       |                   |                             |
|                                                                                                                    | 300 V                 | 20 A                  | 28 - 12           | -                           |
| Use group C                                                                                                        |                       |                       |                   |                             |
|                                                                                                                    | 300 V                 | 20 A                  | 28 - 12           | -                           |

|                                                                                                                                 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>EAC</b><br>Approval ID: KZ7500651131219505 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                    |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>cULus Recognized</b><br>Approval ID: E60425 |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                    |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>cULus Recognized</b><br>Approval ID: E60425 |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UDK 3 - Feed-through terminal block



2775375

<https://www.phoenixcontact.com/au/products/2775375>

## Environmental product compliance

### EU RoHS

|                                         |      |
|-----------------------------------------|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | 49c60520-49af-4b2e-a629-76e5aa1b3a50 |

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd

Unit 7, 2-8 South Street

Rydalmere NSW 2116

1300 786 411

[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)