

S-ME 6 - Switching lock



3034439

<https://www.phoenixcontact.com/au/products/3034439>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Switching lock, width: 8.2 mm, height: 12 mm, color: white



Commercial data

Item number	3034439
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE2ZWX
Product key	BE2ZWX
Catalog page	Page 116 (C-1-2019)
GTIN	4046356151856
Weight per piece (including packing)	0.51 g
Weight per piece (excluding packing)	0.46 g
Customs tariff number	39269097
Country of origin	PL

S-ME 6 - Switching lock

3034439

<https://www.phoenixcontact.com/au/products/3034439>



Technical data

Product properties

Product type	Switching lock
--------------	----------------

Dimensions

Width	8.2 mm
Height	12 mm

Material specifications

Color	white (RAL 9010)
Material	PA
Flammability rating according to UL 94	V0
Insulating material	PA
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

S-ME 6 - Switching lock



3034439

<https://www.phoenixcontact.com/au/products/3034439>

Classifications

ECLASS

ECLASS-13.0	27250392
-------------	----------

ETIM

ETIM 9.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

S-ME 6 - Switching lock



3034439
<https://www.phoenixcontact.com/au/products/3034439>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au