

SB-ME 2-6 - Bridge bar



3035755

<https://www.phoenixcontact.com/au/products/3035755>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bridge bar, pitch: 6.2 mm, number of positions: 2, length: 21 mm, color: gray/orange

Your advantages

- Feed-through terminal blocks of the same shape are available
- Clear
- Easy operation
- Clear selection thanks to printed switching symbols
- Compact design
- Flexible and comprehensive accessories
- Reliably snapped into the end positions
- Contact made via screw terminal points

Commercial data

Item number	3035755
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE2Z2X
Product key	BE2Z2X
Catalog page	Page 105 (C-1-2019)
GTIN	4046356521833
Weight per piece (including packing)	6.7 g
Weight per piece (excluding packing)	6.6 g
Customs tariff number	85366990
Country of origin	PL

Technical data

Product properties

Product type	Bridge bar
Number of positions	2
Pitch	6.2 mm
Potentials	1

Electrical properties

Maximum load current	25 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
----------------------	---

Connection data

Maximum load current	25 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)
----------------------	---

Dimensions

Width	12.3 mm
Height	21.2 mm
Depth	36.4 mm
Length	21.2 mm
Pitch	6.2 mm

Material specifications

Color	multicolored
	gray (RAL 7042)
	orange (RAL 2003)
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

SB-ME 2-6 - Bridge bar



3035755

<https://www.phoenixcontact.com/au/products/3035755>

Mounting

Mounting type	Plug-in mounting
---------------	------------------

SB-ME 2-6 - Bridge bar



3035755

<https://www.phoenixcontact.com/au/products/3035755>

Classifications

ECLASS

ECLASS-13.0	27250303
-------------	----------

ETIM

ETIM 9.0	EC000489
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SB-ME 2-6 - Bridge bar



3035755

<https://www.phoenixcontact.com/au/products/3035755>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au