3240315

https://www.phoenixcontact.com/au/products/3240315

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable duct for installation and mounting in control cabinets, blue, comprising upper part and mounting base, width: 60 mm, height: 80 mm, length: 2000 mm

Your advantages

- · Predetermined breaking point enables tool-free, burr-free removal of bars
- Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- · Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- · The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- · Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

Commercial data

| Item number | 3240315 |
|--------------------------------------|---------------------|
| Packing unit | 18 pc |
| Minimum order quantity | 18 pc |
| Sales key | BE7432 |
| Product key | BE7432 |
| Catalog page | Page 581 (C-3-2019) |
| GTIN | 4046356507950 |
| Weight per piece (including packing) | 1,358 g |
| Weight per piece (excluding packing) | 1,400 g |
| Customs tariff number | 39259020 |
| Country of origin | DE |

3240315

https://www.phoenixcontact.com/au/products/3240315



Technical data

Product properties

| Product type | Wiring duct | | | |
|--|------------------------|--|--|--|
| Dimensions | | | | |
| Width | 60 mm | | | |
| Height | 80 mm | | | |
| Length | 2000 mm | | | |
| Material specifications | | | | |
| Color | blue (RAL 5015) | | | |
| Material | PVC | | | |
| Flammability rating according to UL 94 | V0 | | | |
| Components | Lead-free | | | |
| Cable/line | | | | |
| Halogen-free | no | | | |
| Mechanical properties | | | | |
| Usage cross-section | 4179 mm² (100 %) | | | |
| Number of cables at 60% filling volume | 156 (2.5 mm² Ø 3.4 mm) | | | |
| Environmental and real-life conditions | | | | |
| Ambient conditions | | | | |
| Ambient temperature (operation) | -25 °C 60 °C | | | |
| | | | | |

3240315

https://www.phoenixcontact.com/au/products/3240315



Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/3240315



3240315

https://www.phoenixcontact.com/au/products/3240315



Classifications

ECLASS

| | ECLASS-13.0 | 27400703 | | |
|--------|-------------|----------|--|--|
| ETIM | | | | |
| | ETIM 9.0 | EC000012 | | |
| UNSPSC | | | | |
| | UNSPSC 21.0 | 39131700 | | |

3240315

https://www.phoenixcontact.com/au/products/3240315



Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions | | |
|---|--|--|--|
| China RoHS | | | |
| Environment friendly use period (EFUP) | EFUP-E | | |
| | No hazardous substances above the limits | | |
| EU REACH SVHC | | | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% | | |

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au