5148888

https://www.phoenixcontact.com/au/products/5148888

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mobile thermal transfer printer for card materials, including power supply unit, Euro/US power cable, and USB cable. User manual printed in German and English. Magazine for UCT-TM... sheets and magazine for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon cartridge = 70 m

Product description

THERMOMARK PRIME was developed for mobile or stationary operation. It is equipped with a 7" color touch display, integrated "MARKING system app" marking software on board, and a replaceable battery pack. You can easily create high-quality printed labels and markers in UCT, US, and UM format.

Scope of supply:

THERMOMARK PRIME, power supply - TMP/EXT.POWER-SUPPLY 100-240V (0803672), power cable (pin connector pattern type "F") and power cable (pin connector pattern type "B"), USB cable, ink ribbon cartridge - TMP-RIBBON 110 BK 100 (0803374), magazine - TMP-US-MAG1 (0803341), magazine - TMP-UCT-MAG1 (0803342), terminal marker - UCT-TM 6 (0828736), plastic label - US-EMLP (85,6X54) (0828806), printed and bound manual in English and German, support CD

Your advantages

- Easy data entry, thanks to fully integrated marking software (MARKING system app) and multi-touch display with stand. Additional control possible via PROJECT complete
- Flexible areas of application with more than 600 different marking materials for marking a wide range of applications
- · Maintenance-free operation with proven thermal transfer printer technology in 300 dpi print resolution
- · 100 % independent, thanks to replaceable high-performance rechargeable batteries
- · Material and ink ribbon can be changed easily in less than 10 seconds
- · Automatic ink ribbon, magazine and material detection prevents printing errors
- · Fast, high-quality, and durable printing; printing time for one card is less than 8 seconds

Commercial data

Item number	5148888
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG1221
Product key	BG1221
Catalog page	Page 34 (C-3-2019)
GTIN	4055626041834
Weight per piece (including packing)	9,634 g
Weight per piece (excluding packing)	9,000 g
Customs tariff number	84433210
Country of origin	DE

5148888

https://www.phoenixcontact.com/au/products/5148888

Technical data

Product type	Printing system
Scope of delivery	THERMOMARK PRIME, power supply unit (pin connector pattern type F and pin connector pattern type B, USB cable, TMP-RIBBON 110 BK 100 (0803374), TMP-US-MAG1 (0803341), TMP-UCT-MAG1 (0803342), UCT-TM 6 (0828736) US-EMLP (85,6X54) (0828806), printed and bound manual in German and English, support CD
<i>l</i> arking	
Identification technology	Thermal transfer for sheets and cards
Device properties	
Print width	104 mm
Print resolution	300 dpi
Operating system	Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022
	100 V AC 240 V AC (50 Hz 60 Hz)
Supply Supply voltage range	100 V AC 240 V AC (50 Hz 60 Hz)
Supply Supply voltage range	100 V AC 240 V AC (50 Hz 60 Hz) 10/100 Mbps Ethernet, USB 2.0
Supply Supply voltage range erfaces Interface	
Supply Supply voltage range erfaces Interface	
erfaces Interface	10/100 Mbps Ethernet, USB 2.0
Supply Supply voltage range erfaces Interface mensions Width	10/100 Mbps Ethernet, USB 2.0 380 mm
Supply Supply voltage range erfaces Interface width Height Length	10/100 Mbps Ethernet, USB 2.0 380 mm 122 mm
Supply Supply voltage range erfaces Interface mensions Width Height	10/100 Mbps Ethernet, USB 2.0 380 mm 122 mm

Ambient conditions	
Ambient temperature (operation)	5 °C 40 °C

PHŒNIX CONTACT

5148888

https://www.phoenixcontact.com/au/products/5148888

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/5148888



EAC-RoHS Approval ID: RU D-DE.HB49.B.00023

5148888

https://www.phoenixcontact.com/au/products/5148888



Classifications

ECLASS

ECLASS-11.0	19140104
ECLASS-12.0	19140104
ECLASS-13.0	19140104

ETIM

	ETIM 9.0	EC001684		
UN	UNSPSC			
	UNSPSC 21.0	43212100		

5148888

https://www.phoenixcontact.com/au/products/5148888

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	f5f1dcf0-f260-414b-84ef-f77131664f1e

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au

