#### 0830687

https://www.phoenixcontact.com/au/products/0830687

HŒR

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker label, Sheet, white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, PLOTMARK, cable diameter range: 3 ... 3 mm, mounting type: adhesive, cable diameter:  $\leq$  3 mm, Number of individual labels: 156, text field height: 9.5 mm, text field width: 13 mm

### Your advantages

- · For indoor applications: high resistance to dirt and abrasion due to the protective laminate
- · Firmly defined positioning of labels thanks to the adhesive system
- Broad diameter range with many different applications inside and outside the control cabinet
- · The protective foil is wound over the labeling and provides permanent protection against dirt and abrasion
- · The wrap-around labels do not create any additional volume, so the cable can also be pulled through cable ducts, for example
- · For cylindrical objects, single wires, and cables

### Commercial data

Item number	0830687
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG2314
Product key	BG2314
Catalog page	Page 216 (C-3-2019)
GTIN	4046356718721
Weight per piece (including packing)	15.09 g
Weight per piece (excluding packing)	15.09 g
Customs tariff number	39199080
Country of origin	DE

0830687

https://www.phoenixcontact.com/au/products/0830687

# 

### Technical data

norol	Drint image may your demanding an last sub-tra-
General	Print image may vary depending on laser printer
duct properties	
Product type	Conductor marking
Туре	Label
arking	
Number of individual labels	156
Number of individual labels per row	12
Identification technology	Office laser printing
ensions	
Width	13 mm
Length	19 mm
Aternal dimensions	2
Outside diameter	2 mm 3 mm
ext field	
Text field width	13 mm
Text field height	9.5 mm
erial specifications	
RoHS compliant	yes
Adhesive	Acrylic
Color	white (RAL 9010)
Material	Polyester
Components	Free from halogen and cadmium
le/line	
External cable diameter	≤ 3.00 mm
	3 mm 3 mm
ironmental and real-life conditions	
est for substances that would hinder coating with paint or varnish	
Result	Test passed
V resistance	
Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions



#### 0830687

https://www.phoenixcontact.com/au/products/0830687

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

resting in a condensation on anging climate in the presence of same	
Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2
Salt spray test	
Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Ambient conditions	
Ambient temperature (operation)	-40 °C 150 °C
Ambient temperature (assembly)	5 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging i recommended)
Shelf life	2 years
andards and regulations	
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
punting	
Mounting type	adhesive

0830687

https://www.phoenixcontact.com/au/products/0830687



### Classifications

#### ECLASS

	ECLASS-13.0	27281102			
ETIM					
	ETIM 9.0	EC001530			
UNSPSC					
	UNSPSC 21.0	39131500			

0830687

https://www.phoenixcontact.com/au/products/0830687



### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au