

# PATO 2/15 - Conductor marker carrier



1013122

<https://www.phoenixcontact.com/au/products/1013122>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Conductor marker carrier, transparent, unlabeled, cable diameter range: 2.8 ... 4.4 mm, mounting type: clip on, text field height: 4 mm, text field width: 15 mm

## Your advantages

- Can be labeled using UC-WMT ... or US-WMT ... plastic labels or the EMT ... insert strips
- These marking collars are used for subsequent labeling of systems that have already been wired

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1013122             |
| Packing unit                         | 1,000 pc            |
| Minimum order quantity               | 1,000 pc            |
| Sales key                            | BG221A              |
| Product key                          | BG221A              |
| Catalog page                         | Page 249 (C-3-2019) |
| GTIN                                 | 4017918013547       |
| Weight per piece (including packing) | 0.31 g              |
| Weight per piece (excluding packing) | 0.26 g              |
| Customs tariff number                | 39269097            |
| Country of origin                    | DE                  |

1013122

<https://www.phoenixcontact.com/au/products/1013122>

## Technical data

### Product properties

|              |                      |
|--------------|----------------------|
| Product type | Marker carrier cable |
| Type         | Profile              |

### Dimensions

|        |        |
|--------|--------|
| Width  | 15 mm  |
| Height | 6.3 mm |
| Depth  | 9.2 mm |

### External dimensions

|                        |                   |
|------------------------|-------------------|
| Outside diameter       | 2.8 mm ... 4.4 mm |
| External diameter min. | 2.8 mm            |
| External diameter max. | 5 mm              |

### Text field

|                   |       |
|-------------------|-------|
| Text field width  | 15 mm |
| Text field height | 4 mm  |

### Material specifications

|                                        |               |
|----------------------------------------|---------------|
| Color                                  | transparent   |
| Material                               | PVC           |
| Flammability rating according to UL 94 | V0            |
| Components                             | Silicone-free |

### Cable/line

|                         |                   |
|-------------------------|-------------------|
| External cable diameter | 2.8 mm ... 4.4 mm |
|-------------------------|-------------------|

### Environmental and real-life conditions

#### Ambient conditions

|                                                     |                  |
|-----------------------------------------------------|------------------|
| Ambient temperature (operation)                     | -50 °C ... 80 °C |
| Recommended ambient temperature (storage/transport) | 23 °C            |
| Recommended humidity (storage/transport)            | 50 %             |

### Mounting

|               |         |
|---------------|---------|
| Mounting type | clip on |
|---------------|---------|

# PATO 2/15 - Conductor marker carrier



1013122

<https://www.phoenixcontact.com/au/products/1013122>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281105 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002248 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PATO 2/15 - Conductor marker carrier



1013122

<https://www.phoenixcontact.com/au/products/1013122>

## Environmental product compliance

|                                         |                            |
|-----------------------------------------|----------------------------|
| EU RoHS                                 |                            |
| Fulfills EU RoHS substance requirements | Yes, No exemptions         |
| EU REACH SVHC                           |                            |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt% |
| EF3.0 Climate Change                    |                            |
| CO2e kg                                 | 0.002 kg CO2e              |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)