

1202888

https://www.phoenixcontact.com/au/products/1202888

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimping tool, for turned contacts, universal cross-section setting, up to a maximum of 6.0 mm², digital display with 0.01 mm increments, pressure lock can be unlocked, positioning tool necessary as an accessory for contact positioning

Your advantages

- · Electronic wear monitoring with recalibration function
- · Process reliability with pressure lock and setting lock
- · Basic setting testing with accompanying test pin
- · Safe and simple handling with digital display and optional positioning aid
- · Rotating positioning aid ensures precise contact positioning in the crimping area

Commercial data

| Item number | 1202888 |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | BH3135 |
| Product key | BH3135 |
| GTIN | 4063151267711 |
| Weight per piece (including packing) | 1,140.7 g |
| Weight per piece (excluding packing) | 1,140.7 g |
| Customs tariff number | 82032000 |
| Country of origin | DE |



1202888

https://www.phoenixcontact.com/au/products/1202888

Technical data

Notes

| Note on application | The packing slip includes a detailed list of crimp contacts for turned crimp contacts from 0.14 mm ² 4.0 mm ² of the series CK1.6 ED, CK2.5 ED, CK4.0 ED, CC1.5-TS-2,10, CC1.5- TS-2,50, |
|-------------------------|---|
| Note on application | Use with locator only; see accessories for selection |
| Utilization restriction | |
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |

Product properties

| Product type | Crimping tool |
|------------------|--|
| Compression | Four-mandrel crimping |
| Product property | Electronic wear monitoring with recalibration function |
| | Unlockable pressure lock |
| | Optional positioning tool |

Crimping position 1

| Min. cross section | 0.14 mm ² |
|--------------------|----------------------|
| Max. cross section | 6 mm ² |
| AWG min | 26 |
| AWG max | 10 |

Connection data

Conductor connection

| Cross section range, metric | 0.14 mm² 6 mm² |
|-----------------------------|----------------|
| Cross section range AWG | 26 10 |

Dimensions

| Width | 94 mm |
|--------|--------|
| Height | 28 mm |
| Length | 236 mm |

Material specifications

| Color | black (RAL 9005) |
|----------|------------------|
| Material | Steel |



1202888

https://www.phoenixcontact.com/au/products/1202888

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/1202888

EAC Approval ID: RU x-DE.xx08.B.02974



1202888

https://www.phoenixcontact.com/au/products/1202888

Classifications

ECLASS

| | ECLASS-13.0 | 21043811 |
|----|-------------|----------|
| ET | ГІМ | |
| | ETIM 9.0 | EC000168 |
| U | NSPSC | |
| | UNSPSC 21.0 | 27111500 |



1202888

https://www.phoenixcontact.com/au/products/1202888

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes |
|---|--|
| Exemption | 6(a)-l |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 894d1c6f-7088-4bbd-a917-a42c74c7be7c |
| | |

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au