

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330

<https://www.phoenixcontact.com/au/products/1426330>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, Universal, 8-position, Socket straight M12, coding: A, Insulation displacement connection, knurl material: Stainless steel 1.4404, external cable diameter 3 mm ... 7 mm

## Your advantages

- Safe use in the field, thanks to a high degree of protection
- Insulation displacement connection: innovative and time-saving assembly without stripping the single wire

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1426330       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | AF2CCA        |
| Product key                          | AF2CCA        |
| GTIN                                 | 4055626458632 |
| Weight per piece (including packing) | 29 g          |
| Weight per piece (excluding packing) | 22.22 g       |
| Customs tariff number                | 85366990      |
| Country of origin                    | DE            |

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330  
<https://www.phoenixcontact.com/au/products/1426330>

## Technical data

### Notes

|               |                                                                                                                                                                                                                                         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Assembly note | <b>NOTE:</b> Observe the permissible bending radii when routing cables, since the degree of protection may be at risk if the bending forces are too high. Reduce mechanical loads upstream of the connector, e.g., by using cable ties. |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|


### Product properties

|                      |                                 |
|----------------------|---------------------------------|
| Product type         | Circular connector (cable-side) |
| Sensor type          | Universal                       |
| Number of positions  | 8                               |
| No. of cable outlets | 1                               |
| Shielded             | no                              |
| Coding               | A                               |
| Cable outlet         | straight                        |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Dimensions

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing      |  |
| Length                   | 58 mm                                                                                |
| Wrench size, union nut   | 16 mm                                                                                |
| Wrench size, counter nut | 15 mm                                                                                |

### External dimensions

|                  |               |
|------------------|---------------|
| Outside diameter | 3 mm ... 7 mm |
|------------------|---------------|

### Material specifications

|                                        |                        |
|----------------------------------------|------------------------|
| Flammability rating according to UL 94 | V0                     |
| Seal material                          | FKM                    |
|                                        | FKM                    |
| Material of grip body                  | PA-GF                  |
| Contact material                       | CuSn                   |
| Contact surface material               | Ni/Au                  |
| Contact carrier material               | PA 6.6                 |
| Material for screw connection          | Stainless steel 1.4404 |
| Wire insulation material               | PVC / PE / PP / rubber |

### Connection data

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330

<https://www.phoenixcontact.com/au/products/1426330>

## Conductor connection

|                              |                                                          |
|------------------------------|----------------------------------------------------------|
| Connection method            | Insulation displacement connection                       |
| Connection cross section     | 0.14 mm <sup>2</sup> ... 0.25 mm <sup>2</sup> (flexible) |
| Connection cross section AWG | 26 ... 24 (flexible)                                     |
| Tightening torque            | 0.4 Nm (M12 knurl)<br>4 Nm (Pressure nut)                |

## Pin assignment

|                                                           |        |
|-----------------------------------------------------------|--------|
| Contact   Color (signal designation)   Contact (optional) | 2 = BN |
|                                                           | 3 = GN |
|                                                           | 4 = YE |
|                                                           | 5 = GY |
|                                                           | 6 = PK |
|                                                           | 7 = BU |
|                                                           | 8 = RD |

## Electrical properties

|                                |                    |
|--------------------------------|--------------------|
| Rated surge voltage            | 0.8 kV             |
| Insulation resistance          | ≥ 100 MΩ           |
| Nominal voltage U <sub>N</sub> | 30 V AC<br>30 V DC |
| Nominal current I <sub>N</sub> | 2 A                |

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 100 |
|-----------------------------|-------|

## Connector

### Connection 1

|                   |          |
|-------------------|----------|
| Head design       | Socket   |
| Head cable outlet | straight |
| Head thread type  | M12      |
| Coding            | A        |

## Cable/line

|                      |           |
|----------------------|-----------|
| Signal type/category | Universal |
|----------------------|-----------|

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65                             |
| Ambient temperature (operation) | -40 °C ... 85 °C (Plug / socket) |
| Ambient temperature (assembly)  | -5 °C ... 50 °C                  |

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330

<https://www.phoenixcontact.com/au/products/1426330>

## Standards and regulations

|                          |                              |
|--------------------------|------------------------------|
| Standard designation     | M12 connector                |
| Standards/specifications | according to IEC 61076-2-101 |


# SACC-M12FS-8QO-0,25-CM VA - Connector

1426330

<https://www.phoenixcontact.com/au/products/1426330>


## Drawings

Dimensional drawing



M12 x 1 socket, straight


Functional drawing



1426330

<https://www.phoenixcontact.com/au/products/1426330>

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330

<https://www.phoenixcontact.com/au/products/1426330>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27440116 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121413 |
|-------------|----------|

# SACC-M12FS-8QO-0,25-CM VA - Connector



1426330  
<https://www.phoenixcontact.com/au/products/1426330>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)