

IB IL 24/230 DOR1/W-PAC - Relay module



2861881
<https://www.phoenixcontact.com/au/products/2861881>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Inline, Relay terminal, Relay output: 1 (floating), Changeover contact, 24 V AC, 230 V AC, for switching ohmic loads, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

Product description

The terminal is designed for use within an Inline station. It has one floating relay changeover contact.

Your advantages

- Safe isolation
- Floating connection for one actuator
- Nominal current at the output: 3 A
- Total current of the terminal: 3 A
- Diagnostic and status indicators

Commercial data

Item number	2861881
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DRI133
Product key	DRI133
Catalog page	Page 133 (C-6-2019)
GTIN	4017918894580
Weight per piece (including packing)	79.6 g
Weight per piece (excluding packing)	46 g
Customs tariff number	85389099
Country of origin	DE

IB IL 24/230 DOR1/W-PAC - Relay module



2861881

<https://www.phoenixcontact.com/au/products/2861881>

Technical data

Dimensions

Dimensional drawing	
Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm
Note on dimensions	Housing dimensions

Notes

Note on application	
Note on application	Only for industrial use
Utilization restriction	
CCCex note	Use in potentially explosive areas is not permitted in China.

Interfaces

Inline local bus	
Number of interfaces	2
Connection method	Inline data jumper
Transmission speed	500 kbps

System properties

Module	
ID code (dec.)	189
ID code (hex)	BD
Length code (hex)	C2
Length code (dec)	194
Process data channel	2 bit
Input address area	0 Byte
Output address area	2 bit (Only bit0 is occupied)
Register length	2 bit
Required parameter data	3 Byte
Required configuration data	4 Byte

Output data

IB IL 24/230 DOR1/W-PAC - Relay module



2861881

<https://www.phoenixcontact.com/au/products/2861881>

Relay

Number of outputs	1 (floating)
Connection method	Spring-cage connection
Contact switching type	Changeover contact
Switching voltage	max. 250 V DC
	min. 5 V DC

Product properties

Product type	I/O component
Product family	Inline
Type	modular
Scope of supply	including Inline connector and labeling field
No. of channels	1
Special properties	for switching ohmic loads

Electrical properties

Maximum power dissipation for nominal condition	0.9 W
---	-------

Potentials: Communications power (U_L)

Supply voltage	7.5 V DC (via voltage jumper)
Current draw	max. 60 mA

Electrical isolation/isolation of the voltage ranges

Test voltage: Relay contact / Bus logics	4 kV, 50 Hz, 1 min
Test voltage: Contact/contact	1 kV, 50 Hz, 1 min
Test voltage: Contact / PE	1 kV, 50 Hz, 1 min

Connection data

Connection technology

Connection name	Inline connector
-----------------	------------------

Conductor connection

Connection method	Spring-cage connection
Conductor cross section rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Inline connector

Connection method	Spring-cage connection
Conductor cross section, rigid	0.08 mm ² ... 1.5 mm ²
Conductor cross section, flexible	0.08 mm ² ... 1.5 mm ²
Conductor cross section AWG	28 ... 16
Stripping length	8 mm

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Degree of protection	IP20
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	75 % ... 85 % (in the range of -25°C ... +55°C, appropriate measures against increased humidity (> 85%) must be taken.)
Permissible humidity (storage/transport)	75 % ... 85 % (slight temporary condensation may sometimes appear on the housing)

Standards and regulations

Protection class	I (IEC 61140, EN 61140, VDE 0140-1)
------------------	-------------------------------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

IB IL 24/230 DOR1/W-PAC - Relay module

2861881


<https://www.phoenixcontact.com/au/products/2861881>

Drawings

Dimensional drawing




Connection diagram



2861881

<https://www.phoenixcontact.com/au/products/2861881>

Block diagram



IB IL 24/230 DOR1/W-PAC - Relay module



2861881

<https://www.phoenixcontact.com/au/products/2861881>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2861881>



DNV GL

Approval ID: TAA00000BN



BV

Approval ID: 21725/C0 BV

ABS

Approval ID: 22-2226444-PDA



cULus Recognized

Approval ID: E140324



cULus Listed

Approval ID: E199827

IB IL 24/230 DOR1/W-PAC - Relay module



2861881
<https://www.phoenixcontact.com/au/products/2861881>

Classifications

ECLASS

ECLASS-13.0	27242604
-------------	----------

ETIM

ETIM 9.0	EC001599
----------	----------

UNSPSC

UNSPSC 21.0	32151600
-------------	----------

IB IL 24/230 DOR1/W-PAC - Relay module



2861881

<https://www.phoenixcontact.com/au/products/2861881>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	13c16034-a8ca-443c-a470-e16f445a66c3

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au