

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Safe coupling relay for SIL 2 high- and low-demand applications, couples digital output signals to the periphery, two enabling current paths, one signal contact, module for safe state off applications, integrated test pulse filter, plug-in screw connection, width: 17.5 mm

## Your advantages

- Narrow 17.5 mm housing
- Up to SIL 2 in accordance with EN 61508
- Easy proof test according to IEC 61508 thanks to integrated signal contact
- Long service life thanks to filtering of controller test pulses
- Force-guided contacts in accordance with EN 50205
- 2 enabling current paths
- Couples digital output signals from failsafe controllers to I/O devices (valves, etc.) for electrical isolation and power adaptation

## Commercial data

Item number	2986575
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNA161
Product key	DNA161
Catalog page	Page 255 (C-6-2019)
GTIN	4046356553322
Weight per piece (including packing)	141.05 g
Weight per piece (excluding packing)	136.3 g
Customs tariff number	85364190
Country of origin	DE

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Technical data

### Product properties

Product type	Coupling relay
Product family	PSRclassic
Application	Safe switch off
	High demand
	Low demand
Control	1-channel
Mechanical service life	10x 10 <sup>6</sup> cycles
Relay type	Electromechanical relay with force-guided contacts in accordance with IEC/EN 61810-3

### Insulation characteristics

Overvoltage category	III
Degree of pollution	2

### Times

Typ. starting time with U <sub>s</sub>	50 ms (with U <sub>s</sub> when controlled via A1)
Typical release time	50 ms (with U <sub>s</sub> when controlled via A1)
Recovery time	1 s

### Electrical properties

Maximum power dissipation for nominal condition	2.4 W
Nominal operating mode	100% operating factor
Rated insulation voltage	250 V AC
Rated surge voltage/insulation	Safe isolation, reinforced insulation 6 kV between the control circuits (A1/A2), (31/32), (13/14, 23/24)

### Supply

Designation	A1/A2
Rated control circuit supply voltage U <sub>s</sub>	24 V DC -15 % / +10 %
Rated control supply current I <sub>s</sub>	typ. 55 mA (typ. with U <sub>s</sub> )
Power consumption at U <sub>s</sub>	typ. 1.32 W
Inrush current	max. 100 mA (typ. with U <sub>s</sub> )
Filter time	max. 5 ms (in the event of voltage dips at U <sub>s</sub> )
	max. 2 ms (Test pulse width; high test pulse at A1/A2)
	≥ 100 ms (Test pulse width; high test pulse at A1/A2)
	Test pulse rate = 80 x Test pulse width
	max. 5 ms (Test pulse width; low test pulse at A1/A2)
	≥ 50 ms (Test pulse rate; low test pulse at A1/A2)
	Test pulse rate = 15 x Test pulse width
Protective circuit	Surge protection; Suppressor diode, 33 V (A1 - A2)

### Output data

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

Relay: Enabling current paths (13/14, 23/24)

Output description	2 x N/O, undelayed
Number of outputs	2
Contact switching type	2 enabling current paths
Contact material	AgCuNi, + 0.2 µm Au
Switching capacity	min. 75 mW
Inrush current	max. 5 A
Limiting continuous current	5 A
Sq. Total current	50 A <sup>2</sup> (observe derating)
Switching frequency	max. 0.5 Hz
Mechanical service life	10 <sup>7</sup> cycles
Output fuse	10 A gL/gG

Relay: 31/32

Output description	1 N/C signal contact
Number of outputs	1
Contact switching type	1 confirmation current path
Contact material	AgCuNi, + 0.2 µm Au
Switching capacity	min. 75 mW
Inrush current	max. 100 mA
Limiting continuous current	100 mA
Mechanical service life	10 <sup>7</sup> cycles
Output fuse	4 A gL/gG

## Connection data

Connection technology

pluggable	yes
-----------	-----

Conductor connection

Connection method	Screw connection
Conductor cross section rigid	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross-section AWG	24 ... 12
Stripping length	7 mm
Screw thread	M3
Tightening torque	0.5 Nm ... 0.6 Nm

## Signaling

Operating voltage display	1 x yellow LED
---------------------------	----------------

## Dimensions

Width	17.5 mm
Height	99 mm
Depth	114.5 mm

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Material specifications

Color (Housing)	yellow (RAL 1018)
Housing material	PA

## Characteristics

### Safety data

Stop category	0
---------------	---

### Safety data: EN ISO 13849

Category	1 (Diagnostic coverage (DC) of the control unit at A1/A2 must be $\geq 90\%$ )
Performance level (PL)	c (Diagnostic coverage (DC) of the control unit at A1/A2 must be $\geq 90\%$ )

### Safety data: EN 50156

Safety Integrity Level (SIL)	2
------------------------------	---

### Safety data: IEC 61508 - High demand

Safety Integrity Level (SIL)	2 (max. 10% of the entire SIL; diagnostic coverage (DC) of the control unit at A1/A2 must be $\geq 90\%$ )
------------------------------	--

### Safety data: IEC 61508 - Low demand

Safety Integrity Level (SIL)	2 (max. 10% of the entire SIL; diagnostic coverage (DC) of the control unit at A1/A2 must be $\geq 90\%$ )
------------------------------	--

### Safety data: EN IEC 62061

Safety Integrity Level (SIL)	1 (max. 10% of the entire SIL; diagnostic coverage (DC) of the control unit at A1/A2 must be $\geq 90\%$ )
------------------------------	--

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Min. degree of protection of inst. location	IP54
Ambient temperature (operation)	-20 °C ... 55 °C (observe derating)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Maximum altitude	$\leq 2000$ m (Above sea level)
Max. permissible humidity (storage/transport)	75 % (on average, 85% infrequently, non-condensing)
Max. permissible relative humidity (operation)	75 % (on average, 85% infrequently, non-condensing)
Shock	15g
Vibration (operation)	10 Hz ... 150 Hz, 2g

## Approvals

### CE

Identification	CE-compliant
----------------	--------------

## Mounting

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

Mounting type	DIN rail mounting
Mounting position	any

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay




2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Drawings

Circuit diagram



Block diagram


# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay

2986575

<https://www.phoenixcontact.com/au/products/2986575>




Circuit diagram



Single-channel connection with integration of the confirmation current path

Circuit diagram



Two-channel connection with integration of the confirmation current path

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2986575>



**DNV GL**

Approval ID: TAA00002UC



**cULus Listed**

Approval ID: E140324



**Functional Safety**

Approval ID: 968/EZ 365.11/24



# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Classifications

### ECLASS

ECLASS-13.0	27371819
-------------	----------

### ETIM

ETIM 8.0	EC001449
----------	----------

### UNSPSC

UNSPSC 21.0	39122200
-------------	----------

# PSR-SCP- 24DC/FSP2/2X1/1X2 - Coupling relay



2986575

<https://www.phoenixcontact.com/au/products/2986575>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	ab3cdbf8-f1d5-4306-8965-a56b3a796f13

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd

Unit 7, 2-8 South Street

Rydalmere NSW 2116

1300 786 411

[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)