

PAIS-4-FIX RD - Test adapter

3032793

<https://www.phoenixcontact.com/au/products/3032793>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, number of positions: 1, color: red

Your advantages

- Make contact and latch securely to any point in the function shaft
- Test adapter for accommodating safety test plugs with a 4 mm diameter

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 3032793 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BE2Z3X |
| Product key | BE2Z3X |
| Catalog page | Page 413 (C-1-2019) |
| GTIN | 4046356996709 |
| Weight per piece (including packing) | 2.47 g |
| Weight per piece (excluding packing) | 2.36 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |

PAIS-4-FIX RD - Test adapter

3032793

<https://www.phoenixcontact.com/au/products/3032793>



Technical data

Notes

| | |
|---------|---|
| General | Do not plug in while the power is connected |
| General | Latching coding element, therefore only suitable for being plugged in once |
| General | Latching testing accessories, therefore only suitable for being plugged in once |

Product properties

| | |
|---------------------|-------------|
| Product type | Test socket |
| Number of positions | 1 |

Electrical properties

| | |
|----------------------|-------|
| Maximum load current | 10 A |
| Max. voltage | 250 V |

Connection data

| | |
|----------------------|--------------------|
| Maximum load current | 10 A |
| Connection method | Plug-in connection |

Dimensions

| | |
|--------------|---------|
| Width | 6 mm |
| Height | 6.5 mm |
| Depth | 53.3 mm |
| Diameter | 5.8 mm |
| Pin diameter | 2.4 mm |

Material specifications

| | |
|--|----------------|
| Color | red (RAL 3001) |
| Material | Copper alloy |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |

Mechanical properties

Mechanical data

| | |
|-----------------------------|---|
| Insertion/withdrawal cycles | 1 |
|-----------------------------|---|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|--|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
|---------------------------------|--|

PAIS-4-FIX RD - Test adapter



3032793

<https://www.phoenixcontact.com/au/products/3032793>

| | |
|--|---|
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 90 % |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

PAIS-4-FIX RD - Test adapter



3032793

<https://www.phoenixcontact.com/au/products/3032793>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27250304 |
|-------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002555 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 20122000 |
|-------------|----------|

PAIS-4-FIX RD - Test adapter



3032793
<https://www.phoenixcontact.com/au/products/3032793>

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au