


# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 76 A, number of connections: 2, connection method: Screw connection, Rated cross section: 16 mm<sup>2</sup>, cross section: 1.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: red

## Your advantages

- The reducing bridges can be used to connect terminal blocks with different connection technologies, e.g., UT 35 screw terminal block with Push-in technology 2,5 Push-in terminal blocks, to form power blocks
- The flexible options for reducing bridging in the CLIPLINE complete system can be found in "Accessories for the CLIPLINE complete modular terminal block system"
- Easy and time-saving potential supply and distribution of large currents and cross sections up to 35 mm<sup>2</sup> with reducing bridges

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3044207       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE1111        |
| Product key                          | BE1111        |
| GTIN                                 | 4046356892148 |
| Weight per piece (including packing) | 30.18 g       |
| Weight per piece (excluding packing) | 30.08 g       |
| Customs tariff number                | 85369010      |
| Country of origin                    | TR            |

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Product family        | UT                          |
| Area of application   | Machine building            |
|                       | Plant engineering           |
|                       | Process industry            |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 2.43 W |

### Connection data

|                                 |                    |
|---------------------------------|--------------------|
| Number of connections per level | 2                  |
| Nominal cross section           | 16 mm <sup>2</sup> |

### Level 1 above 1 below 1

|                                                                                           |                                                         |
|-------------------------------------------------------------------------------------------|---------------------------------------------------------|
| Screw thread                                                                              | M5                                                      |
| Tightening torque                                                                         | 2.5 ... 3 Nm                                            |
| Stripping length                                                                          | 14 mm                                                   |
| Internal cylindrical gage                                                                 | A7                                                      |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                           |
| Conductor cross section rigid                                                             | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>              |
| Cross section AWG                                                                         | 14 ... 4 (converted acc. to IEC)                        |
| Conductor cross section flexible                                                          | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>              |
| Conductor cross section, flexible [AWG]                                                   | 14 ... 4 (converted acc. to IEC)                        |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 1 mm <sup>2</sup> ... 16 mm <sup>2</sup>                |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 1 mm <sup>2</sup> ... 16 mm <sup>2</sup>                |
| 2 conductors with same cross section, solid                                               | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>                 |
| 2 conductors with same cross section, flexible                                            | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>                 |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>                 |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.75 mm <sup>2</sup> ... 10 mm <sup>2</sup>             |
| Nominal current                                                                           | 76 A                                                    |
| Maximum load current                                                                      | 101 A (with 25 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 1000 V                                                  |

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

|                       |                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------|
| Note                  | Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area. |
| Nominal cross section | 16 mm <sup>2</sup>                                                                                                           |

## Ex data

### Rated data (ATEX/IECEx)

|                             |                                     |
|-----------------------------|-------------------------------------|
| Identification              | Ex II 2 GD Ex eb IIC Gb             |
| Operating temperature range | -60 °C ... 110 °C                   |
| Ex-certified accessories    | 3047206 D-UT 16                     |
|                             | 1205066 SZS 1,0X4,0 VDE             |
|                             | 3022276 CLIPFIX 35-5                |
|                             | 3022218 CLIPFIX 35                  |
| List of bridges             | Plug-in bridge / FBS 2-12 / 3005950 |
| Bridge data                 | 73.5 A (16 mm <sup>2</sup> )        |
| Ex temperature increase     | 40 K (80.5 A / 16 mm <sup>2</sup> ) |
| for bridging with bridge    | 690 V                               |
| Rated insulation voltage    | 630 V                               |
| output                      | (Permanent)                         |

### Ex level General

|                      |         |
|----------------------|---------|
| Rated voltage        | 690 V   |
| Rated current        | 73.5 A  |
| Maximum load current | 89.5 A  |
| Contact resistance   | 0.16 mΩ |

### Ex connection data General

|                                                       |                                            |
|-------------------------------------------------------|--------------------------------------------|
| Torque range                                          | 2.5 Nm ... 3 Nm                            |
| Nominal cross section                                 | 16 mm <sup>2</sup>                         |
| Rated cross section AWG                               | 6                                          |
| Connection capacity rigid                             | 1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 4                                   |
| Connection capacity flexible                          | 1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup> |
| Connection capacity AWG                               | 16 ... 6                                   |
| 2 conductors with same cross section, solid           | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>    |
| 2 conductors with the same cross-section AWG rigid    | 18 ... 10                                  |
| 2 conductors with same cross section, stranded        | 1 mm <sup>2</sup> ... 4 mm <sup>2</sup>    |
| 2 conductors with the same cross-section AWG flexible | 18 ... 12                                  |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 12.2 mm |
| End cover width    | 2.2 mm  |
| Height             | 55.5 mm |
| Depth              | 54.4 mm |
| Depth on NS 35/7,5 | 55 mm   |
| Depth on NS 35/15  | 62.5 mm |

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

## Material specifications

|                                                                         |                |
|-------------------------------------------------------------------------|----------------|
| Color                                                                   | red (RAL 3001) |
| Flammability rating according to UL 94                                  | V0             |
| Insulating material group                                               | I              |
| Insulating material                                                     | PA             |
| Static insulating material application in cold                          | -60 °C         |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C         |
| Relative insulation material temperature index (Elec., UL 746 B)        | 125 °C         |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                 |                                     |
|-------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test               | Increase in temperature $\leq 45$ K |
| Result                                          | Test passed                         |
| Short-time withstand current 16 mm <sup>2</sup> | 1.92 kA                             |
| Result                                          | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2.2 kV      |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 1.5 mm <sup>2</sup> / 0.4 kg |
|                                | 16 mm <sup>2</sup> / 2.9 kg  |
|                                | 25 mm <sup>2</sup> / 4.5 kg  |
| Result                         | Test passed                  |

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2018-05            |
| Spectrum               | Long life test category 2, bogie-mounted       |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | $6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$      |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |

### Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 30g                               |
| Shock duration                 | 18 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C ( )                                                                                                          |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UT 16 RD - Feed-through terminal block

3044207

<https://www.phoenixcontact.com/au/products/3044207>



## Drawings

Circuit diagram



# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/3044207>

### DNV

Approval ID: TAE00001S9



### IECEE CB Scheme

Approval ID: DE1-65779

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 76 A                  | -                 | - 16                        |



### cULus Recognized

Approval ID: E60425

|                            | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B                |                       |                       |                   |                             |
|                            | 600 V                 | 85 A                  | 16 - 4            | -                           |
| Multi-conductor connection | 600 V                 | 85 A                  | - 14              | -                           |
| Use group C                |                       |                       |                   |                             |
|                            | 600 V                 | 85 A                  | 16 - 4            | -                           |
| Multi-conductor connection | 600 V                 | 85 A                  | - 14              | -                           |



### LR

Approval ID: LR24100022TA



### VDE approval of drawings

Approval ID: 40020166

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 1000 V                | 76 A                  | -                 | 1.5 - 16                    |



### ATEX

Approval ID: KEMA04ATEX2048U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 73.5 A                | -                 | 1.5 - 16                    |
| Only rigid conductors    | 690 V                 | 89.5 A                | -                 | 1.5 - 25                    |



### cUL Recognized

Approval ID: E192998

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 85 A                  | 16 - 4            | -                           |



## IECEx

Approval ID: IECEx KEM 06.0027U

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Only flexible conductors | 690 V                 | 73.5 A                | -                 | 1.5 - 16                    |
| Only rigid conductors    | 690 V                 | 89.5 A                | -                 | 1.5 - 25                    |



## UL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 600 V                 | 85 A                  | 16 - 4            | -                           |



## CCC

Approval ID: 2020322313000622



## UKCA-EX

Approval ID: DEKRA 21UKEX0304U



## EAC Ex

Approval ID: KZ 7500525010101950

# UT 16 RD - Feed-through terminal block



3044207

<https://www.phoenixcontact.com/au/products/3044207>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UT 16 RD - Feed-through terminal block



3044207  
<https://www.phoenixcontact.com/au/products/3044207>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)