

RB UT 10-(2,5/4) - Reducing bridge

3047060

<https://www.phoenixcontact.com/au/products/3047060>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Reducing bridge, pitch: 10.2 mm, number of positions: 2, length: 29 mm, color: red

Commercial data

Item number	3047060
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE1Z2X
Product key	BE1Z2X
Catalog page	Page 27 (C-3-2013)
GTIN	4017918975685
Weight per piece (including packing)	3.04 g
Weight per piece (excluding packing)	2.812 g
Customs tariff number	85366990
Country of origin	PL

RB UT 10-(2,5/4) - Reducing bridge

3047060

<https://www.phoenixcontact.com/au/products/3047060>



Technical data

Product properties

Product type	Reducing bridge
Number of positions	2
Pitch	10.2 mm

Electrical properties

Maximum load current	The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.
----------------------	--

Connection data

Maximum load current	The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.
----------------------	--

Dimensions

Width	15.1 mm
Height	29.3 mm
Depth	3 mm
Length	29.3 mm
Pitch	10.2 mm

Material specifications

Color	red (RAL 3001)
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C ()
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	Plug-in mounting
---------------	------------------

RB UT 10-(2,5/4) - Reducing bridge



3047060

<https://www.phoenixcontact.com/au/products/3047060>

Classifications

ECLASS

ECLASS-13.0	27250303
-------------	----------

ETIM

ETIM 9.0	EC000489
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RB UT 10-(2,5/4) - Reducing bridge



3047060
<https://www.phoenixcontact.com/au/products/3047060>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au