

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 32 A, number of connections: 3, connection method: Push-in connection, Rated cross section: 4 mm<sup>2</sup>, 1 level, cross section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- 2, 3, and 4-conductor terminal blocks with the same shape
- Ground terminal blocks of the same shape are available
- The PTS 2,5, which is equipped with four bridge shafts, offers a wide range of potential bridging options
- Angled conductor entry for use in flat terminal boxes
- Large space saving when used in concealed wiring systems

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3213604             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE2212              |
| Product key                          | BE2212              |
| Catalog page                         | Page 107 (C-1-2019) |
| GTIN                                 | 4055626085463       |
| Weight per piece (including packing) | 10.25 g             |
| Weight per piece (excluding packing) | 10.264 g            |
| Customs tariff number                | 85369010            |
| Country of origin                    | PL                  |

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Technical data

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Product family        | PTS                            |
| Area of application   | Machine building               |
|                       | Plant engineering              |
|                       | Process industry               |
| Number of connections | 3                              |
| Number of rows        | 1                              |
| Potentials            | 1                              |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.02 W |

### Connection data

|                                 |                   |
|---------------------------------|-------------------|
| Number of connections per level | 3                 |
| Nominal cross section           | 4 mm <sup>2</sup> |

#### 1 level

|                                                                                           |                                                              |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Stripping length                                                                          | 10 mm ... 12 mm                                              |
| Internal cylindrical gage                                                                 | A4                                                           |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                                |
| Conductor cross section rigid                                                             | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>                    |
| Cross section AWG                                                                         | 24 ... 10 (converted acc. to IEC)                            |
| Conductor cross section flexible                                                          | 0.2 mm <sup>2</sup> ... 6 mm <sup>2</sup>                    |
| Conductor cross section, flexible [AWG]                                                   | 24 ... 10 (converted acc. to IEC)                            |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>                   |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.25 mm <sup>2</sup> ... 4 mm <sup>2</sup>                   |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 1 mm <sup>2</sup>                    |
| Nominal current                                                                           | 32 A                                                         |
| Maximum load current                                                                      | 38 A (with 6 mm <sup>2</sup> conductor cross section, rigid) |
| Nominal voltage                                                                           | 800 V                                                        |
| Nominal cross section                                                                     | 4 mm <sup>2</sup>                                            |

#### 1 level Connection cross sections directly pluggable

|                                                                   |                                           |
|-------------------------------------------------------------------|-------------------------------------------|
| Conductor cross section rigid                                     | 0.5 mm <sup>2</sup> ... 6 mm <sup>2</sup> |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.5 mm <sup>2</sup> ... 4 mm <sup>2</sup> |

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Ex data

### Rated data (ATEX/IECEx)

|                                                    |                                     |
|----------------------------------------------------|-------------------------------------|
| Identification                                     | Ex II 2 GD Ex eb IIC Gb             |
| Operating temperature range (1)                    | -60 °C ... 85 °C                    |
| Operating temperature range (2)                    | -40 °C ... 110 °C                   |
| Ex-certified accessories                           | 3213600 D-PTS 4                     |
|                                                    | 3024481 ATP-ST 6                    |
|                                                    | 1204517 SZF 1-0,6X3,5               |
|                                                    | 3022276 CLIPFIX 35-5                |
|                                                    | 3022218 CLIPFIX 35                  |
| List of bridges                                    | Plug-in bridge / FBS 2-6 / 3030336  |
|                                                    | Plug-in bridge / FBS 3-6 / 3030242  |
|                                                    | Plug-in bridge / FBS 4-6 / 3030255  |
|                                                    | Plug-in bridge / FBS 5-6 / 3030349  |
|                                                    | Plug-in bridge / FBS 10-6 / 3030271 |
|                                                    | Plug-in bridge / FBS 20-6 / 3030365 |
| Bridge data                                        | 27 A (4 mm²)                        |
| Ex temperature increase                            | 40 K (30 A / 4 mm²)                 |
| for bridging with bridge                           | 550 V                               |
| - At bridging between non-adjacent terminal blocks | 352 V                               |
| - At cut-to-length bridging with cover             | 325 V                               |
| - At cut-to-length bridging with partition plate   | 325 V                               |
| Rated insulation voltage                           | 500 V                               |
| output                                             | (Permanent)                         |

### Ex level General

|                      |              |
|----------------------|--------------|
| Rated voltage        | 550 V        |
| Rated current        | 28 A (4 mm²) |
| Maximum load current | 33 A (6 mm²) |
| Contact resistance   | 0.71 mΩ      |

### Ex connection data General

|                                                                                      |                   |
|--------------------------------------------------------------------------------------|-------------------|
| Nominal cross section                                                                | 4 mm²             |
| Rated cross section AWG                                                              | 12                |
| Connection capacity rigid                                                            | 0.2 mm² ... 6 mm² |
| Connection capacity AWG                                                              | 24 ... 10         |
| Connection capacity flexible                                                         | 0.2 mm² ... 4 mm² |
| Connection capacity AWG                                                              | 24 ... 12         |
| Conductor cross section flexible, with ferrule without plastic sleeve min.           | 0.25 mm²          |
| Conductor cross section flexible, with ferrule without plastic sleeve max.           | 6 mm²             |
| Single conductor/terminal point, flexible, with ferrule, without plastic sleeve, AWG | 24 ... 10         |

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 62.4 mm |
| Depth on NS 35/7,5 | 43 mm   |
| Depth on NS 35/15  | 50.5 mm |

## Material specifications

|                                                                         |                 |
|-------------------------------------------------------------------------|-----------------|
| Color                                                                   | gray (RAL 7042) |
| Flammability rating according to UL 94                                  | V0              |
| Insulating material group                                               | I               |
| Insulating material                                                     | PA              |
| Static insulating material application in cold                          | -60 °C          |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C          |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3     |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg        |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                |                                     |
|------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test              | Increase in temperature $\leq 45$ K |
| Result                                         | Test passed                         |
| Short-time withstand current 4 mm <sup>2</sup> | 0.48 kA                             |
| Short-time withstand current 6 mm <sup>2</sup> | 0.72 kA                             |
| Result                                         | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.2 mm <sup>2</sup> / 0.2 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg   |
|                                | 6 mm <sup>2</sup> / 1.4 kg   |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 30g                                 |
| Shock duration                 | 18 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Drawings

Circuit diagram



# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/3213604>

|  <b>CSA</b><br>Approval ID: 2030668 |                       |                       |                   |                             |
|----------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                      | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                          | 600 V                 | 30 A                  | 24 - 10           | -                           |
|                                                                                                                      |                       |                       |                   |                             |
| Use group C                                                                                                          | 600 V                 | 30 A                  | 24 - 10           | -                           |
|                                                                                                                      |                       |                       |                   |                             |

|                                                                                                                                   |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>EAC</b><br>Approval ID: RU C-DE.BL08.B.00644 |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>cULus Recognized</b><br>Approval ID: E60425 |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                    | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                        | 600 V                 | 30 A                  | 24 - 10           | -                           |
|                                                                                                                                    |                       |                       |                   |                             |
| Use group C                                                                                                                        | 600 V                 | 30 A                  | 24 - 10           | -                           |
|                                                                                                                                    |                       |                       |                   |                             |

|                                       |  |  |  |  |
|---------------------------------------|--|--|--|--|
| <b>DNV</b><br>Approval ID: TAE000010T |  |  |  |  |
|---------------------------------------|--|--|--|--|

|                                                                                                                                    |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>IECEx</b><br>Approval ID: IECExKIWA17.0026U |  |  |  |  |
|------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>ATEX</b><br>Approval ID: KIWA17ATEX0048U |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>CCC</b><br>Approval ID: 2020322313000631 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                                                                                                                                     |  |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|  <b>UKCA-EX</b><br>Approval ID: CSAE 21UKEX3607U |  |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|



# PTS 4-TWIN - Feed-through terminal block

3213604

<https://www.phoenixcontact.com/au/products/3213604>



**EAC Ex**

Approval ID: KZ 7500525010101950

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PTS 4-TWIN - Feed-through terminal block



3213604

<https://www.phoenixcontact.com/au/products/3213604>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)