


# CD 120X80 - Cable duct



3240202

<https://www.phoenixcontact.com/au/products/3240202>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable duct for installation and mounting in control cabinets, gray, comprising upper part and mounting base, width: 120 mm, height: 80 mm, length: 2000 mm

## Your advantages

- Predetermined breaking point enables tool-free, burr-free removal of bars
- Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

## Commercial data

Item number	3240202
Packing unit	8 pc
Minimum order quantity	8 pc
Sales key	BE7431
Product key	BE7431
Catalog page	Page 581 (C-3-2019)
GTIN	4046356459266
Weight per piece (including packing)	2,213 g
Weight per piece (excluding packing)	2,687.5 g
Customs tariff number	39259020
Country of origin	DE

# CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/au/products/3240202>



## Technical data

### Product properties

Product type	Wiring duct
--------------	-------------

### Dimensions

Width	120 mm
Height	80 mm
Length	2000 mm

### Material specifications

Color	stone gray (RAL 7030)
Material	PVC
Flammability rating according to UL 94	V0
Components	Lead-free

### Cable/line

Halogen-free	no
--------------	----

### Mechanical properties

Usage cross-section	8676 mm <sup>2</sup> (100 %)
Number of cables at 60% filling volume	318 (2.5 mm <sup>2</sup> Ø 3.4 mm)

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
---------------------------------	------------------


# CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/au/products/3240202>



## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/3240202>



**CSA**

Approval ID: 80202282



**VDE approval of drawings**

Approval ID: 40058456



**UL Recognized**

Approval ID: E328576

# CD 120X80 - Cable duct

3240202

<https://www.phoenixcontact.com/au/products/3240202>



## Classifications

### ECLASS

ECLASS-13.0	27400703
-------------	----------

### ETIM

ETIM 9.0	EC000012
----------	----------

### UNSPSC

UNSPSC 21.0	39131700
-------------	----------

# CD 120X80 - Cable duct



3240202  
<https://www.phoenixcontact.com/au/products/3240202>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)