

0801505

https://www.phoenixcontact.com/au/products/0801505

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marker for end clamp, Sheet, white, unlabeled, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, mounting type: latching, Number of individual labels: 24, text field height: 5 mm, text field width: 30 mm

Your advantages

- The UCT-EM (30x5) ... UniCard marking card provides markers for the CLIPFIX 35-5 ... end bracket
- · The markers, which are supplied in uniform sheets, can be marked quickly, easily, and precisely using the card printers
- · The sheets provide additional space for project information and function text that can be helpful during further assembly
- · The multi-section marking strips are easy to fit and can be easily separated if required
- · Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications

Commercial data

| Item number | 0801505 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BG2418 |
| Product key | BG2418 |
| Catalog page | Page 152 (C-3-2019) |
| GTIN | 4046356673525 |
| Weight per piece (including packing) | 11.218 g |
| Weight per piece (excluding packing) | 11 g |
| Customs tariff number | 39269097 |
| Country of origin | PL |



0801505

https://www.phoenixcontact.com/au/products/0801505

Technical data

Product properties

| Product type | Device marking |
|-------------------------------------|--|
| Area of application | CLIPFIX 35-5 end bracket |
| Marking | |
| Number of individual labels | 24 |
| Number of individual labels per row | 8 |
| Identification technology | Thermal transfer for sheets and cards, UV LED technology, direct laser marking |

Mounting

| Mounting type | latching | |
|---------------|----------|--|

Material specifications

| RoHS compliant | yes |
|--|--------------------------------|
| Color | white (RAL 9010) |
| Material | PC |
| Flammability rating according to UL 94 | V0 |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Components | free from silicone and halogen |

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

| Result | Test passed |
|---|--|
| UV resistance | |
| Specification | ISO 4892-2:2013-03 (following) |
| Result | Test passed |
| Test duration | 96 h |
| Wipe resistance of inscriptions | |
| Specification | IEC 61010-1:2010-06 |
| | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl [CAS No. 67-63-0] | Test passed |
| n-Hexane [CAS No. 110-54-3] | Test passed |
| Water + Petroleum ether [CAS No. 64742-82-1] | Test passed |

Testing in a condensation changing climate in the presence of sulfur dioxide



0801505

https://www.phoenixcontact.com/au/products/0801505

| Specification | DIN 50018:2013-05 |
|---|-----------------------------|
| Result | Test passed |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Salt spray test | |
| Specification | DIN EN 60068-2-11:2000-02 |
| Result | Test passed |
| Ambient conditions | |
| Ambient temperature (operation) | -40 °C 120 °C |
| Recommended ambient temperature (storage/transport) | 23 °C |
| Recommended humidity (storage/transport) | 50 % |
| vimensions | |
| Width | 30 mm |
| Height | 5 mm |
| Depth | 4.55 mm |
| Text field | |
| Text field width | 30 mm |
| Text field height | 5 mm |
| tandards and regulations | |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Standards | |
| Standards/regulations | EN 45545-2 |
| | |



0801505

https://www.phoenixcontact.com/au/products/0801505

Classifications

| | ECLASS-13.0 | 27281101 |
|----|-------------|----------|
| ΕΊ | ГІМ | |
| | ETIM 9.0 | EC000761 |
| U | NSPSC | |
| | UNSPSC 21.0 | 39131500 |



0801505

https://www.phoenixcontact.com/au/products/0801505

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|---|--------------------|
| | |
| | |
| EU REACH SVHC | |

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au