

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104

<https://www.phoenixcontact.com/au/products/0832104>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wire marking, Sheet, white, unlabeled, can be labeled with: BLUEMARK E.CARD, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME 2.0, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, TOPMARK NEO, TOPMARK LASER, cable diameter range: 4.1 ... 4.7 mm, mounting type: clip on, Number of individual labels: 18, text field height: 4 mm, text field width: 23 mm

## Your advantages

- The UCT-WMCO ... UniCard labeling range includes markers for the subsequent labeling of conductors by simply snapping on
- Large-surface labeling option in a space-saving design
- Marking service: Phoenix Contact can custom-mark all UniCard markers according to your specifications
- Secure tight fit even in the event of vibrations
- The format automatically ensures printing with a high degree of positioning accuracy

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0832104             |
| Packing unit                         | 6 pc                |
| Minimum order quantity               | 6 pc                |
| Sales key                            | BG2218              |
| Product key                          | BG2218              |
| Catalog page                         | Page 209 (C-3-2019) |
| GTIN                                 | 4055626258638       |
| Weight per piece (including packing) | 13.994 g            |
| Weight per piece (excluding packing) | 1.448 g             |
| Customs tariff number                | 39269097            |
| Country of origin                    | PL                  |

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104

<https://www.phoenixcontact.com/au/products/0832104>

## Technical data

### Product properties

|              |                   |
|--------------|-------------------|
| Product type | Conductor marking |
| Type         | Card form         |

### Marking

|                                     |    |
|-------------------------------------|----|
| Number of individual labels         | 18 |
| Number of individual labels per row | 6  |

### Dimensions

|        |         |
|--------|---------|
| Width  | 23 mm   |
| Height | 6.85 mm |
| Depth  | 7.62 mm |

### External dimensions

|                  |                   |
|------------------|-------------------|
| Outside diameter | 4.1 mm ... 4.7 mm |
|------------------|-------------------|

### Text field

|                   |       |
|-------------------|-------|
| Text field width  | 23 mm |
| Text field height | 4 mm  |

### Material specifications

|                                                        |                                          |
|--------------------------------------------------------|------------------------------------------|
| Color                                                  | white (RAL 9010)                         |
| Material                                               | PC                                       |
| Flammability rating according to UL 94                 | V0                                       |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3                              |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3                              |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3                              |
| Components                                             | free from silicone, halogen, and cadmium |

### Cable/line

|                         |                   |
|-------------------------|-------------------|
| External cable diameter | 4.1 mm ... 4.7 mm |
|-------------------------|-------------------|

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

#### Test for substances that would hinder coating with paint or varnish

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

#### Scratch test for the determining scratch resistance

|               |                                |
|---------------|--------------------------------|
| Specification | EN ISO 1518-1:2023 (following) |
| Requirements  | ≥ 5 N                          |
| Result        | Test passed                    |

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104

<https://www.phoenixcontact.com/au/products/0832104>

## Tesa film test

|               |                                     |
|---------------|-------------------------------------|
| Specification | DIN EN ISO 2409:2020-12 (following) |
| Result        | Test passed                         |

## UV resistance

|               |                                       |
|---------------|---------------------------------------|
| Specification | DIN EN ISO 4892-2:2021-11 (following) |
| Result        | Test passed                           |
| Test duration | 96 h                                  |

## Temperature resistance

|                        |                                 |
|------------------------|---------------------------------|
| Specification          | ANSI/UL 969-2018:03 (following) |
| Test duration          | 240 h                           |
| Rating 100 °C (121 °C) | Test passed                     |

## Wipe resistance of inscriptions

|                                                   |                                                |
|---------------------------------------------------|------------------------------------------------|
| Specification                                     | DIN EN 61010-1 (VDE 0411-01):2020-03           |
|                                                   | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl<br>[CAS No. 67-63-0]                    | Test passed                                    |
| n-Hexane<br>[CAS No. 110-54-3]                    | Test passed                                    |
| Water + Petroleum ether<br>[CAS No. 64742-82-1]   | Test passed                                    |
| Sodium hydroxide 0.1 mol/l<br>[CAS No. 1310-73-2] | Test passed                                    |
| Ethanol (99 %)<br>[CAS No. 64-17-5]               | Test passed                                    |
| Specification                                     | ISO 175:2010 (following)                       |
| Test duration                                     | 168 h                                          |
| IRM 901                                           | Test passed                                    |
| IRM 902                                           | Test passed                                    |

## Testing in a condensation changing climate in the presence of sulfur dioxide

|               |                      |
|---------------|----------------------|
| Specification | EN ISO 22479:2022-06 |
| Result        | Test passed          |
| Procedure     | Method B             |
| Cycles        | 2                    |

## Salt spray test

|               |                           |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result        | Test passed               |
| Test duration | 96 h                      |

## Ambient conditions

|                                                     |                                                                                 |
|-----------------------------------------------------|---------------------------------------------------------------------------------|
| Ambient temperature (operation)                     | -40 °C ... 100 °C                                                               |
| Recommended ambient temperature (storage/transport) | 23 °C                                                                           |
| Recommended humidity (storage/transport)            | 50 % (Storage in a dry and dark place in the original packaging is recommended) |

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104

<https://www.phoenixcontact.com/au/products/0832104>

|            |         |
|------------|---------|
| Shelf life | 2 years |
|------------|---------|

## Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

## Standards

|                       |            |
|-----------------------|------------|
| Standards/regulations | EN 45545-2 |
|-----------------------|------------|

## Mounting

|               |         |
|---------------|---------|
| Mounting type | clip on |
|---------------|---------|

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104

<https://www.phoenixcontact.com/au/products/0832104>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281102 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001530 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

# UCT-WMCO 4,7 (23X4) - Wire marking



0832104  
<https://www.phoenixcontact.com/au/products/0832104>

## Environmental product compliance

|                                         |                            |
|-----------------------------------------|----------------------------|
| EU RoHS                                 |                            |
| Fulfills EU RoHS substance requirements | Yes, No exemptions         |
| EU REACH SVHC                           |                            |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt% |
| EF3.0 Climate Change                    |                            |
| CO2e kg                                 | 0.063 kg CO2e              |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)