

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 8-position, PVC, black RAL 9005, free cable end, on Socket straight M12, coding: A, cable length: 10 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components

Commercial data

Item number	1415727
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AF1CFA
Product key	AF1CFA
Catalog page	Page 209 (C-2-2019)
GTIN	4055626052496
Weight per piece (including packing)	542.3 g
Weight per piece (excluding packing)	521 g
Customs tariff number	85444290
Country of origin	PL

1415727

<https://www.phoenixcontact.com/au/products/1415727>

Technical data

Product properties

Product type	Sensor/actuator cable
Application	Standard
Number of positions	8
No. of cable outlets	1
Shielded	no
Coding	A

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	30 V AC
	30 V DC
Nominal current I_N	2 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Signaling

Status display	no
Status display present	no

Connector

Connection 1

Type	free cable end
------	----------------

Connection 2

Type	Socket straight M12
Number of positions	8

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Coding type	A
-------------	---

Cable/line

Cable length	10 m
--------------	------

PVC black [PVC]

Dimensional drawing		
Cable weight	54 kg/km	
UL AWM Style	2464 / 1729 (80°C/300 V)	
Number of positions	8	
Shielded	no	
Cable type	PVC black [PVC]	
Conductor structure signal line	14x 0.15 mm	
AWG signal line	24	
Conductor cross section	8x 0.25 mm ² (Signal line)	
Wire diameter incl. insulation	1.17 mm ±0.05 mm	
External cable diameter	5.90 mm ±0.2 mm	
Outer sheath, material	PVC	
External sheath, color	black RAL 9005	
Conductor material	Bare Cu litz wires	
Material wire insulation	PVC	
Single wire, color	white, brown, green, yellow, gray, pink, blue, red	
Thickness, insulation	≥ 0.23 mm	
Thickness, outer sheath	≥ 0.76 mm	
Overall twist	8 wires around filler to the core	
Max. conductor resistance	79 Ω/km (at 20 °C)	
Insulation resistance	≥ 200 MΩ*km (at 20 °C)	
Nominal voltage, cable	≤ 300 V AC	
Test voltage	≥ 3000 V AC	
Minimum bending radius, fixed installation	5 x D	
Minimum bending radius, flexible installation	10 x D	
Smallest bending radius, fixed installation	30 mm	
Smallest bending radius, movable installation	59 mm	
Flame resistance	as per VW-1 in accordance with UL 758	
Resistance to oil	in accordance with DIN EN 60811-2-1	
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation)	
	-10 °C ... 80 °C (Cable, flexible installation)	

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Environmental and real-life conditions

Ambient conditions


Degree of protection	IP65
	IP67
	IP68
Ambient temperature (operation) (male connector/female connector)	-25 °C ... 90 °C (Plug / socket)

Standards and regulations

Standard designation	M12 connector
Standards/specifications	IEC 61076-2-101


Drawings

Dimensional drawing



M12 x 1 socket, straight

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side


SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Circuit diagram



Contact assignment of the M12 socket

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/1415727>



UL Listed

Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-



cUL Listed

Approval ID: FILE E 221474

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	30 V	2 A	-	-



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Classifications

ECLASS

ECLASS-13.0	27060311
-------------	----------

ETIM

ETIM 9.0	EC001855
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

SAC-8P-10,0-PVC/M12FS - Sensor/actuator cable



1415727

<https://www.phoenixcontact.com/au/products/1415727>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

EF3.0 Climate Change

CO2e kg	5.771 kg CO2e
---------	---------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au