

2904891

https://www.phoenixcontact.com/au/products/2904891

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

450 mm long Rogowski coil. The measuring coil diameter when installed is 140 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Commercial data

Item number	2904891
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CMMA12
Product key	CMMA12
Catalog page	Page 219 (C-5-2019)
GTIN	4046356898188
Weight per piece (including packing)	169 g
Weight per piece (excluding packing)	169 g
Customs tariff number	90309000
Country of origin	IT



https://www.phoenixcontact.com/au/products/2904891



Technical data

Product properties

Product type	Rogowski coil
Set comprises	2904922 PACT RCP-4000A-1A-D140
Insulation characteristics	
Pollution degree	2

Electrical properties

Measuring coil

Conductor structure signal line	2x 0.22 mm (Signal (tinned))
	1x 0.22 mm (Shielding (tinned))
Insulation	double insulation
Rated insulation voltage	1000 V AC (rms CAT III)
	600 V AC (rms CAT IV)
Test voltage	10.45 kV DC (60 s)
Accuracy class	0.2 (IEC 61869-10: A1)

General

Converter type	Rogowski coil

Input data

Frequency

Designation	Measuring coil
Frequency measuring range	40 Hz 20000 Hz
Current transformer	
Converter type	Rogowski coil

Output data

Signal

Designation	Measuring coil
Output signal (at 50 Hz)	100 mV (no load, at 1,000 A)
Output voltage (in no-load operation)	$V_{OUT} = M * dI/dt$
Output voltage (sinusoidal, in no-load operation)	100 mV (V _{OUT} = 2 * π * M * f * I (M = 0.318 μ H; example: At 50 Hz; I = 1,000 A))

Dimensions

Measuring coil

Length	450 mm
Diameter	8.3 mm ±0.2 mm

Measuring coil when installed



2904891



https://www.phoenixcontact.com/au/products/2904891

Diameter	140 mm
Signal line	
Length	3 m
Material specifications	
Housing material	PC
Coil material	Elastollan
Environmental and real-life conditions Ambient conditions	
Measuring coil degree of protection	IP54 (not assessed by UL)
Ambient temperature (operation) (Measuring coil)	-30 °C 80 °C (Measuring coil)
Ambient temperature (storage/transport)	-40 °C 80 °C (Measuring coil)
Altitude	< 2000 m

Approvals

U	K	CA

Certificate	UKCA-compliant
CMIM	
Certificate	CMIM-compliant CMIM-compliant
UL, USA/Canada	
Identification	UL 61010 Recognized
Note	Measuring coil
tandards and regulations	

5 % ... 95 % (non-condensing)

Standards and regulations

Permissible humidity (operation)

Standards/regulations	IEC 61010-2-030
	IEC 61869-10



https://www.phoenixcontact.com/au/products/2904891



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/au/products/2904891



cUL Recognized

Approval ID: FILE E 357804



UL RecognizedApproval ID: FILE E 357804



2904891

https://www.phoenixcontact.com/au/products/2904891

Classifications

	ECLASS-13.0	27210992	
ETIM			
	ETIM 9.0	EC002498	
UNSPSC			
	UNSPSC 21.0	39121000	



https://www.phoenixcontact.com/au/products/2904891



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au