

REL-IR/LDP-125DC/4X21/MS - Single relay



1819310

<https://www.phoenixcontact.com/au/products/1819310>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in industrial relay with power contacts, 4 changeover contacts, test button, status LED, freewheeling diode, mechanical switching position indicator, polarity: A1+, A2-, coil voltage: 125 V DC

Commercial data

| | |
|------------------------|---|
| Item number | 1819310 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | DK6949 |
| Product key | DK6949 |
| GTIN | 4067923449886 |
| Customs tariff number | 85364900 |
| Country of origin | Information on the country of origin is provided with the delivery. |

1819310

<https://www.phoenixcontact.com/au/products/1819310>

Technical data

Product properties

| | |
|-------------------------|-----------------------|
| Product type | Single relay |
| Product family | RIFLINE complete |
| Operating mode | 100% operating factor |
| Mechanical service life | approx. 10^7 cycles |

Insulation characteristics

| | |
|----------------------|------------------|
| Insulation | Basic insulation |
| Overvoltage category | III |
| Pollution degree | 2 |

Data management status

| | |
|------------------------------|------------|
| Date of last data management | 01.04.2026 |
|------------------------------|------------|

Electrical properties

| | |
|--|--|
| Service life electrical | see diagram |
| Maximum power dissipation for nominal condition | 0.8625 W |
| Test voltage (Winding/contact) | 2.5 kV _{rms} (50 Hz, 1 min., winding/contact) |
| Test voltage (Changeover contact/changeover contact) | 2 kV _{rms} (50 Hz, 1 min., changeover contact/changeover contact) |
| Rated insulation voltage | 250 V AC |

Input data

Coil side

| | |
|--------------------------------|--------------------------|
| Nominal input voltage U_N | 125 V DC |
| Input voltage range | 93.8 V DC ... 212.5 V DC |
| Drive and function | monostable |
| Drive (polarity) | polarized |
| Typical input current at U_N | 6.1 mA |
| Typical response time | 15 ms |
| Typical release time | 18 ms |
| Protective circuit | Freewheeling diode |
| Status display | LED (yellow) |

Output data

Switching

| | |
|-----------------------------|-----------------------|
| Contact switching type | 4 changeover contacts |
| Type of switch contact | Single contact |
| Contact material | AgNi |
| Maximum switching voltage | 250 V AC/DC |
| Minimum switching voltage | 12 V (10 mA) |
| Limiting continuous current | 4x 6 A |

REL-IR/LDP-125DC/4X21/MS - Single relay



1819310

<https://www.phoenixcontact.com/au/products/1819310>

| | |
|---------------------------------------|----------------------------|
| Maximum inrush current | 12 A (20 ms, N/O contacts) |
| Min. switching current | 10 mA (12 V) |
| Interrupting rating (ohmic load) max. | 144 W (at 24 V DC) |
| | 130 W (at 48 V DC) |
| | 90 W (at 60 V DC) |
| | 66 W (at 110 V DC) |
| | 88 W (at 220 V DC) |
| | 1500 VA (for 250 V AC) |
| Switching power min. | 0.12 W |

Connection data

| | |
|-------------------|--------------------|
| Connection method | Plug-in connection |
|-------------------|--------------------|

Dimensions

Item dimensions

| | |
|--------|---------|
| Width | 22.5 mm |
| Height | 28 mm |
| Depth | 35 mm |

Environmental and real-life conditions

Ambient conditions

| | |
|---|------------------|
| Degree of protection | RT II |
| Ambient temperature (operation) | -40 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Altitude | ≤ 2000 m |

Standards and regulations


| | |
|-----------------------|------------|
| Standards/regulations | EN 61810-1 |
|-----------------------|------------|

Mounting

| | |
|-------------------|---------------------------|
| Mounting type | Plug-in mounting |
| Assembly note | in rows with zero spacing |
| Mounting position | any |


Drawings

Diagram




Operating voltage range

Diagram



Electrical service life

Diagram



- ① AC, ohmic load
- ② DC, ohmic load

Interrupting rating

Diagram



Service life reduction factor

Diagram



Permissible humidity for operation and storage.

The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures $\leq 0^\circ\text{C}$ must be prevented

Area B: Condensation at ambient temperatures $> 0^\circ\text{C}$ must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature $\leq 25^\circ\text{C}$.

Circuit diagram



REL-IR/LDP-125DC/4X21/MS - Single relay



1819310

<https://www.phoenixcontact.com/au/products/1819310>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/1819310>



cULus Recognized

Approval ID: E522914

REL-IR/LDP-125DC/4X21/MS - Single relay



1819310

<https://www.phoenixcontact.com/au/products/1819310>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 27371601 |
| ECLASS-15.0 | 27371601 |

ETIM

| | |
|-----------|----------|
| ETIM 10.0 | EC001437 |
|-----------|----------|

REL-IR/LDP-125DC/4X21/MS - Single relay



1819310

<https://www.phoenixcontact.com/au/products/1819310>

Environmental product compliance

EU RoHS

| | |
|---|--------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(c)-I |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au