

# AI-GB 0,75-10 BU - Ferrule



2100107

<https://www.phoenixcontact.com/au/products/2100107>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, Length contact range: 10 mm, sleeve length: 16 mm, color: blue

## Your advantages

- Due to the increased diameter of the insulating collar, this type of ferrule is specifically used with AWG cables
- These ferrules enable practical crimping of conductors with increased insulation

## Commercial data

|                                      |                                                                     |
|--------------------------------------|---------------------------------------------------------------------|
| Item number                          | 2100107                                                             |
| Packing unit                         | 100 pc                                                              |
| Minimum order quantity               | 100 pc                                                              |
| Sales key                            | BH341S                                                              |
| Product key                          | BH341S                                                              |
| GTIN                                 | 4067923214033                                                       |
| Weight per piece (including packing) | 0.111 g                                                             |
| Weight per piece (excluding packing) | 0.111 g                                                             |
| Customs tariff number                | 85369010                                                            |
| Country of origin                    | Information on the country of origin is provided with the delivery. |

# AI-GB 0,75-10 BU - Ferrule



2100107

<https://www.phoenixcontact.com/au/products/2100107>

## Technical data

### Product properties


|                    |                                                                                               |
|--------------------|-----------------------------------------------------------------------------------------------|
| Product type       | Cable end sleeve                                                                              |
| Conductor category | stranded conductors, class 2, 5, 6 / B, C, K, M                                               |
| Product property   | Suitable for AWG/multi-standard cables due to the increased diameter of the insulating collar |
|                    | UL certified                                                                                  |
|                    | Made from soft tin-plated electrolytic copper                                                 |
|                    | Correspond to the requirements of UL 486F                                                     |
|                    | Plastic collar made of polypropylene                                                          |
|                    | Halogen-free                                                                                  |
|                    | Long/short-term temperature: +105°C/+120°C                                                    |

### Connection data

#### Conductor connection

|                                       |                      |
|---------------------------------------|----------------------|
| Conductor cross-section flexible max. | 0.75 mm <sup>2</sup> |
| Conductor cross-section AWG max.      | 18                   |
| Stripping length                      | 13 mm                |

### Dimensions

|                                           |                                                                                      |
|-------------------------------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing                       |  |
| Sleeve length                             | 16 mm                                                                                |
| Length contact range                      | 10 mm                                                                                |
| Maximum stripping length                  | 13 mm                                                                                |
| Ferrule diameter                          | 1.3 mm                                                                               |
| Sleeve wall thickness                     | 0.15 mm                                                                              |
| Insulating collar thickness               | 0.25 mm                                                                              |
| Inner dimensions of the insulating collar | 3.4 mm                                                                               |

### Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Color                                  | blue (RAL 5015)                |
| Material                               | CU-DHP                         |
| Flammability rating according to UL 94 | HB                             |
| Coating                                | galvanically tin-plated        |
| Surface characteristics                | Tin-plated                     |
| Components                             | free from silicone and halogen |

### Mechanical properties

# AI-GB 0,75-10 BU - Ferrule



2100107

<https://www.phoenixcontact.com/au/products/2100107>

## Technical data


|               |       |
|---------------|-------|
| Sleeve length | 16 mm |
|---------------|-------|

## Standards and regulations

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Design according to standard | Color code in accordance with DIN 46228-4, UL 486F-E |
|------------------------------|------------------------------------------------------|

## Drawings

Dimensional drawing



Sleeve length (b), length contact range (h), insulating collar inner dimension (d), sleeve diameter (k), insulating collar thickness (i), sleeve wall thickness (j)

# AI-GB 0,75-10 BU - Ferrule

2100107

<https://www.phoenixcontact.com/au/products/2100107>



## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/2100107>



**cULus Listed**

Approval ID: E488001

# AI-GB 0,75-10 BU - Ferrule

2100107

<https://www.phoenixcontact.com/au/products/2100107>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27400201 |
| ECLASS-15.0 | 27400201 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC000005 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 27121700 |
|-------------|----------|

# AI-GB 0,75-10 BU - Ferrule

2100107

<https://www.phoenixcontact.com/au/products/2100107>



## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd  
Unit 7, 2-8 South Street  
Rydalmere NSW 2116  
1300 786 411  
[customerservice@phoenixcontact.com.au](mailto:customerservice@phoenixcontact.com.au)