

PRODUCT INFORMATION SHEET

SIPF01

Product:	DOUBLE SIDED POLYETHYLENE FOAM TAPE - ACRYLIC ADHESIVE	
Colour:	White	
Roll Size:	Any Width over 6mm in rolls 50 Metres long	
Application:	Adhering of most plastics, metal, paper - emblems etc. Multipurpose, Economy Grade.	
Description:	Polyethylene foam coated with pressure sensitive acrylic adhesive on both sides. Yellow Silicon paper liner.	
Technical Details:	Tape Thickness:	1.0mm
	Breaking Load:	NA
	Elongation at Break:	130 %
	Adhesion to Steel:	14.4 N / 25mm
	Service Temperature:	-10° to 80°C
	Storage Temperature:	15° to 25° C
	Shelf Life:	12 Months
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15° C and 25° C.	
Note:	The above figures represent average values. Actual figures can vary. The selection and application of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our products and specifications.	