

PRODUCT INFORMATION SHEET

S1392

Product:	DOUBLE SIDED FILMIC MOUNTING TAPE																	
Description:	A white 38-micron hard PVC film carrier with a high tack high shear, highly cross-linked solvent acrylic adhesive. This adhesive gives excellent initial tack and because of its high coat weight of adhesive it is ideal for rough, uneven & textured surfaces. The adhesive has very good temperature, U.V. & plasticiser resistance, and has excellent peel adhesion performance even on low energy surfaces.																	
Liner:	A high-quality 80 gsm kraft paper with differential silicone release treatment																	
Colour:	White																	
Roll Size:	Standard length 33 metres by required width. NB Special lengths available on request																	
Application:	Affixing furniture trims and mouldings, mirror mounting, bonding rough fabrics and cloths & any other surfaces where a strong bond is needed.																	
Technical Details:	<table><tr><td>Tape Thickness:</td><td>0.26mm (AFERA 4006)</td></tr><tr><td>Liner Thickness:</td><td>0.07mm</td></tr><tr><td>Peel Adhesion to Stainless Steel</td><td></td></tr><tr><td> 1 Minute</td><td>14.0 N/cm FINAT TM 1</td></tr><tr><td> 20 Minutes</td><td>16.0 N/cm</td></tr><tr><td> 24 Hours</td><td>18.0 N/cm</td></tr><tr><td>Static Shear 23° C</td><td>> 400hours FINAT TM 8</td></tr><tr><td>Service Temperature:</td><td>-40°C to +70° C</td></tr></table>		Tape Thickness:	0.26mm (AFERA 4006)	Liner Thickness:	0.07mm	Peel Adhesion to Stainless Steel		1 Minute	14.0 N/cm FINAT TM 1	20 Minutes	16.0 N/cm	24 Hours	18.0 N/cm	Static Shear 23° C	> 400hours FINAT TM 8	Service Temperature:	-40°C to +70° C
Tape Thickness:	0.26mm (AFERA 4006)																	
Liner Thickness:	0.07mm																	
Peel Adhesion to Stainless Steel																		
1 Minute	14.0 N/cm FINAT TM 1																	
20 Minutes	16.0 N/cm																	
24 Hours	18.0 N/cm																	
Static Shear 23° C	> 400hours FINAT TM 8																	
Service Temperature:	-40°C to +70° C																	
Surface Preparation:	The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15° C and 25° C.																	
Note:	The above figures represent average values. Actual figures can vary. The selection and application of a tape is the responsibility of the buyer. Tape should be stored at room temperature and should not be exposed to sunlight. We reserve the right to make changes without notice to our products and specifications.																	