

Data Sheet for Article: MM216405--

Plunger Bridge



Technical Data

Series	MM
Illumination	non-illuminated
Make-up	accessories
shock resistance	30G
Ambient temperature Open (°C)	-25°C...+70°C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Standards	IEC/EN 60947, VDE 0660
Mounting position	any
Type No.	M22-XW

Datei Tabelle: Plunger Bridge

			Contact elements	Double Contact elements
False switching safety				
at 24VDC/5mA	H _F Error frequency	1 failure on 10 ⁷ operations	$\leq 10^{-7}$	-
at 5VDC/1mA	H _F Error frequency	1 failure on 5x10 ⁶ operations	$\leq 5 \times 10^{-6}$	-
Maximum short circuit protection device				
Fuseless (automatic circuit breaker)		Type	B6/1	B6/1
Fuse	gG/gL		10	10
Breaking capacity Rated operational current I_e				
AC-15	115V	A	6	6
	230V	A	6	6
	400V	A	4	-
	500V	A	2	-
DC-13	24V	A	3	3
	42V	A	1.7	-
	60V	A	1.2	-
	110V	A	0.8	0.6
	220V	A	0.3	0.3
Lifetime, electrical				
AC-15	230V/0.5A		1.6	-
	230V/1.0A		1	-
	230V/3.0A		0.7	-
DC-13	12V/2.8A		1.2	-

Article Table

DESCRIPTION	Order No.
Plunger Bridge	MM216405