



The image is purely indicative and may not fully reflect the configuration of the product.

Empty 3-way junction box D8-17 IP65

Code: **THA.211.A1A**



Any changes made to the technical data sheet may be made without notice.

GENERAL INFORMATIONS

Installation type	Fixed connection (re-inspectable)
Configuration	Branch without terminal block <i>*Accessories for cable and terminal block to be purchased separately</i>
Color	Black (Plastic components) - Techno Green (Rubber components)
External dimensions (mm)	137.0 x 118.0 x 36.0
Available internal volume (mm)	58.0 x 45.0 x 27.0

ELECTRICAL DATA

Connection points	3
--------------------------	---

CONNECTION DATA

Passing cable stripping length (mm)	30.00
Branch cable stripping length (mm)	30.00
Recommended cable type	H05xxx/H07xxx
MIN cable diameter (mm)	8.00
MAX cable diameter (mm)	5.00pm
Nut-cable gland tightening torque	4.0 Nm
Tightening torque for cover screws	1.0 Nm

ENVIRONMENTAL CONDITIONS

IP protection rating	IP65
Degree of protection IK	IK08
Corrosion resistance	Salt mist test: EN60068-2-11:2000
MIN/MAX temperature (According to EN61984/EN60998)	-40°C/+60°C

MATERIALS

Body	PA66 UL94 V2
Seals	TPE
Cable sealing rubbers	NBR
Property	Halogen Free
Contacts	Brass
Contact screws	Steel
Cover screws	Steel

CONFORMITÀ PRODOTTO

Approvazione IEC	EN 60529:1991 EN 60998-1:2004
------------------	-------------------------------

DATI COMMERCIALI


EAN	8057457091817
Configurazione del prodotto	Confezione industriale (OEM)
Tipo di confezionamento	Scatola
Pezzi/scatola (pz)	50
Peso/pezzo (gr)	109.70
Dimensioni della scatola (mm)	600 x 270 x 400
Codice doganale	85369010
Paese di provenienza	ITALIA

CERTIFICAZIONI

Effettua la login per vedere questa sezione.

DOCUMENTAZIONE TECNICA

Documentazione Tecnica:

File	Formato	Dimensione
 606002000_IST_TH211.pdf	PDF	1.04 MB

MATERIALE DI COMUNICAZIONE

Effettua la login per vedere questa sezione.