



The image is purely indicative and may not fully reflect the configuration of the product.

Compact 4p linear terminal block IP00 screw

Code: **THB.032.A4B**



Any changes made to the technical data sheet may be made without notice.

GENERAL INFORMATIONS

Installation type	Fixed connection (re-inspectable)
Configuration	Entrance - exit (steering wheel)
Color	Brown RAL7021
External dimensions (mm)	20.8 x 50.7 x 21.0

ELECTRICAL DATA

Connection points	2
Circuit application	Power/Signal
Rated current (AC/DC)	32A
Rated voltage (AC/DC)	450V AC
Number of poles	4
Contact symbols	1-2-3-4
Type of contacts	Lives
	<i>*Terminal block with double connection</i>
Thread/Tightening torque	M3 - 0.8 Nm

CONNECTION DATA

MIN flexible conductor section without terminal (mm ²)	0.50
MAX flexible conductor section without terminal (mm ²)	4.00
MIN rigid conductor section (mm ²)	0.50
MAX rigid conductor section (mm ²)	4.00
Wire stripping length (mm)	8.00
Recommended cable type	H05xxx/H07xxx

ENVIRONMENTAL CONDITIONS

IP protection rating	IP00
Corrosion resistance	Salt mist test: EN60068-2-11:2000
T marking	T 125°C
Tracking index	PTI 175

MATERIALS

Body	PA66 GF UL94 V0
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCE

IEC approved	EN 60998-1:2004
--------------	-----------------

COMMERCIAL DATA

EAN	8057457092326
Product configuration	Industrial packaging (OEM)
Type of packaging	Box
Pieces/box (pcs)	400
Weight/piece (g)	31.10
Box dimensions (mm)	400 x 400 x 230
Corresponding KIT packaging	THB.032.A4B.R
Customs code	85369010
country of origin	ITALY

CERTIFICATIONS

Log in to see this section.

COMMUNICATION MATERIAL

Log in to see this section.
